
























REFLEXION XPC

[Feature](#)
[Gallery](#)
[Specifications](#)
[Spec Download](#)
[Download](#)
[FAQ](#)
[Support List](#)

[CPU Support List](#)
[Memory Support](#)
[Graphic card](#)

CPU Support List

Socket	Model number	BIOS	BOM
Celeron	Intel Celeron 2.00 GHz	FB61RS0C 	all version
Celeron	Intel Celeron 2.10 GHz	FB61RS0C 	all version
Celeron	Intel Celeron 2.20 GHz	FB61RS0C 	all version
Celeron	Intel Celeron 2.30 GHz	FB61RS0C 	all version
Celeron	Intel Celeron 2.40 GHz	FB61RS0C 	all version
Celeron	Intel Celeron 2.50 GHz	FB61RS0C 	all version
Celeron	Intel Celeron 2.60 GHz	FB61RS0C 	all version
Celeron	Intel Celeron 2.80 GHz	FB61RS0C 	all version
Pentium 4	Intel Pentium 4 1.80 GHz	FB61RS0C 	all version
Pentium 4	Intel Pentium 4 2.00 GHz	FB61RS0C 	all version
Pentium 4	Intel Pentium 4 2.20 GHz	FB61RS0C 	all version
Pentium 4	Intel Pentium 4 2.26 GHz	FB61RS0C 	all version
Pentium 4	Intel Pentium 4 2.40 GHz	FB61RS0C 	all version
Pentium 4	Intel Pentium 4 2.50 GHz	FB61RS0C 	all version
Pentium 4	Intel Pentium 4 2.53 GHz	FB61RS0C 	all version
Pentium 4	Intel Pentium 4 2.60 GHz	FB61RS0C 	all version
Pentium 4	Intel Pentium 4 2.66 GHz	FB61RS0C 	all version
Pentium 4	Intel Pentium 4 2.80 GHz	FB61RS0C 	all version
Pentium 4	Intel Pentium 4 3.00 GHz	FB61RS0C 	all version
Pentium 4	Intel Pentium 4 3.06 GHz	FB61RS0C 	all version
Pentium 4	Intel Pentium 4 3.20 GHz	FB61RS0C 	all version
Pentium 4	Intel Pentium 4 3.40 GHz	FB61RS0C 	all version
Pentium EE	Intel Pentium 4 Extreme Edition 3.00 GHz	FB61RS0C 	all version

MotherBoard's PCB version: FB61RV2.x

Remarks:

1. Intel Pentium 4/Celeron(478-pin) support Northwood processor with 400/533/800(CPU internal core bus) MHz FSB only. 2. Willamette/Prescott/Celeron D processor are not supported.



Shuttle

Shuttle specializes in the design and manufacturing of robust and IoT-ready small form factor PC, industrial PC, Panel PC, Kiosk, and face recognition integrated solutions.

 NO. 30, Lane 76, Rui Guang Rd.
 Nei-Hu Dist., Taipei, Taiwan

 +886 2 8792 6168

 web@tw.shuttle.com

About Shuttle

[Company Profile](#)

[Contact US](#)

[News](#)

[Investors Relations](#)

[Privacy Policy](#)

[Legal Notices](#)

Support

[Download](#)

[FAQ](#)

[Service Center](#)

[Linux Compatibility](#)