





































SB61G2 V4

Feature Gallery Specifications SpecDownload Download Support List

CPU Support List Memory Support Graphic card Accessory Support

CPU Support List

Socket	Model number	BIOS	BOM
Celeron	Intel Celeron 2.00 GHz	FB61S40B 	all version
Celeron	Intel Celeron 2.10 GHz	FB61S40B 	all version
Celeron	Intel Celeron 2.20 GHz	FB61S40B 	all version
Celeron	Intel Celeron 2.30 GHz	FB61S40B 	all version
Celeron	Intel Celeron 2.40 GHz	FB61S40B 	all version
Celeron	Intel Celeron 2.50 GHz	FB61S40B 	all version
Celeron	Intel Celeron 2.60 GHz	FB61S40B 	all version
Celeron	Intel Celeron 2.80 GHz	FB61S40B 	all version
Celeron D	Intel Celeron D 315 2.26 GHz	FB61S40B 	all version
Celeron D	Intel Celeron D 320 2.40 GHz	FB61S40B 	all version
Celeron D	Intel Celeron D 325 2.53 GHz	FB61S40B 	all version
Celeron D	Intel Celeron D 330 2.66 GHz	FB61S40B 	all version
Celeron D	Intel Celeron D 335 2.80 GHz	FB61S40B 	all version
Celeron D	Intel Celeron D 340 2.93 GHz	FB61S40B 	all version
Celeron D	Intel Celeron D 345 3.06 GHz	FB61S40B 	all version
Pentium 4	Intel Pentium 4 1.80 GHz	FB61S40B 	all version
Pentium 4	Intel Pentium 4 2.00 GHz	FB61S40B 	all version
Pentium 4	Intel Pentium 4 2.20 GHz	FB61S40B 	all version
Pentium 4	Intel Pentium 4 2.26 GHz	FB61S40B 	all version
Pentium 4	Intel Pentium 4 2.40 GHz	FB61S40B 	all version
Pentium 4	Intel Pentium 4 2.40A GHz	FB61S40B 	all version
Pentium 4	Intel Pentium 4 2.50 GHz	FB61S40B 	all version
Pentium 4	Intel Pentium 4 2.53 GHz	FB61S40B 	all version
Pentium 4	Intel Pentium 4 2.60 GHz	FB61S40B 	all version
Pentium 4	Intel Pentium 4 2.66 GHz	FB61S40B 	all version
Pentium 4	Intel Pentium 4 2.80 GHz	FB61S40B 	all version
Pentium 4	Intel Pentium 4 2.80A GHz	FB61S40B 	all version
Pentium 4	Intel Pentium 4 2.80E GHz	FB61S40B 	all version
Pentium 4	Intel Pentium 4 3.00 GHz	FB61S40B 	all version
Pentium 4	Intel Pentium 4 3.00E GHz	FB61S40B 	all version
Pentium 4	Intel Pentium 4 3.06 GHz	FB61S40B 	all version
Pentium 4	Intel Pentium 4 3.20 GHz	FB61S40B 	all version
Pentium 4	Intel Pentium 4 3.20E GHz	FB61S40B 	all version
Pentium 4	Intel Pentium 4 3.40 GHz	FB61S40B 	all version
Pentium 4	Intel Pentium 4 3.40E GHz	FB61S40B 	all version
Pentium EE	Intel Pentium 4 Extreme Edition 3.00 GHz	FB61S40B 	all version

MotherBoard's PCB version: FB61 V4.x

Remarks: 1. CPU internal core bus speed runs at 400/533/800MHz. 2. Willamette core CPUs are not supported.




Shuttle

Shuttle specializes in the design and manufacturing of robust and IoT-ready small form factor PC, industrial PC, Panel PC, Kiosk, and face recognition integrated solutions.

 NO. 30, Lane 76, Rui Guang Rd.
Nei-Hu Dist., Taipei, Taiwan

 +886 2 8792 6168

 web@tw.shuttle.com

About Shuttle

Company Profile

Contact US

News

Investors Relations

Privacy Policy

Legal Notices

Support

Download

FAQ

Service Center

Linux Compatibility