

SS30G2 SE (CHINA & EUROPE EXCLUDE)

Feature Gallery Specifications Spec Download Download Support List

CPU Support List Memory Support Graphic card Accessory Support

CPU Support List

Socket	Model number	BIOS	BOM
Celeron 400 Sequence	Intel Celeron 420 1.60 GHz	SS30S1CB	all version
Celeron 400 Sequence	Intel Celeron 430 1.80 GHz	SS30S1CB	all version
Celeron 400 Sequence	Intel Celeron 440 2.00 GHz	SS30S1CB	all version
Celeron 400 Sequence	Intel Celeron 460 2.40 GHz	SS30S1CB	all version
Celeron D	Intel Celeron D 326 2.53 GHz	SS30S1CA	all version
Celeron D	Intel Celeron D 331 2.66 GHz	SS30S1CA	all version
Celeron D	Intel Celeron D 335 2.80 GHz	SS30S1CA	all version
Celeron D	Intel Celeron D 336 2.80 GHz	SS30S1CA	all version
Celeron D	Intel Celeron D 340 2.93 GHz	SS30S1CA	all version
Celeron D	Intel Celeron D 340J 2.93 GHz	SS30S1CA	all version
Celeron D	Intel Celeron D 346 3.06 GHz	SS30S1CA	all version
Celeron D	Intel Celeron D 347 3.06 GHz	SS30S1CA	all version
Celeron D	Intel Celeron D 351 3.20 GHz	SS30S1CA	all version
Celeron D	Intel Celeron D 352 3.2GHz	SS30S1CA	all version
Celeron D	Intel Celeron D 355 3.33 GHz	SS30S1CA	all version
Celeron D	Intel Celeron D 356 3.33 GHz	SS30S1CA	all version
Core™2 Duo	Intel Core™2 Duo E4300 1.80 GHz	SS30S1CA	BOM14 and later
Core™2 Duo	Intel Core™2 Duo E4400 2.00 GHz	SS30S1CA	BOM14 and later
Core™2 Duo	Intel Core™2 Duo E4500 2.20 GHz	SS30S1CA	BOM14 and later
Pentium 4	Intel Pentium 4 511 2.80 GHz	SS30S1CA	all version
Pentium 4	Intel Pentium 4 524 3.06 GHz	SS30S1CA	all version
Pentium 4	Intel Pentium 4 531 3.00 GHz	SS30S1CA	all version
Pentium 4	Intel Pentium 4 540/540J 3.20 GHz	SS30S1CA	all version
Pentium 4	Intel Pentium 4 541 3.20 GHz	SS30S1CA	all version
Pentium 4	Intel Pentium 4 550/550J 3.40 GHz	SS30S1CA	all version
Pentium 4	Intel Pentium 4 560/560J 3.60 GHz	SS30S1CA	all version
Pentium 4	Intel Pentium 4 571 3.80 GHz	SS30S1CA	all version
Pentium 4	Intel Pentium 4 630 3.00 GHz	SS30S1CA	all version
Pentium 4	Intel Pentium 4 631 3.00 GHz	SS30S1CA	all version
Pentium 4	Intel Pentium 4 641 3.20 GHz	SS30S1CA	all version
Pentium 4	Intel Pentium 4 650 3.40 GHz	SS30S1CA	all version
Pentium 4	Intel Pentium 4 651 3.40 GHz	SS30S1CA	all version
Pentium 4	Intel Pentium 4 660 3.60 GHz	SS30S1CA	all version
Pentium 4	Intel Pentium 4 661 3.60 GHz	SS30S1CA	all version
Pentium 4	Intel Pentium 4 670 3.80 GHz	SS30S1CA	all version
Pentium D	Intel Pentium D 805 2.66 GHz	SS30S1CA	all version
Pentium D	Intel Pentium D 820 2.80 GHz	SS30S1CA	all version
Pentium D	Intel Pentium D 915 2.80 GHz	SS30S1CA	all version
Pentium D	Intel Pentium D 920 2.80 GHz	SS30S1CA	all version
Pentium D	Intel Pentium D 925 3.0 GHz	SS30S1CA	BOM14 and later
Pentium D	Intel Pentium D 930 3.00 GHz	SS30S1CA	all version
Pentium D	Intel Pentium D 935 3.20 GHz	SS30S1CA	BOM14 and later
Pentium D	Intel Pentium D 940 3.20 GHz	SS30S1CA	all version
Pentium D	Intel Pentium D 945 3.40 GHz	SS30S1CA	BOM14 and later
Pentium Dual-Core	Intel Pentium Dual-Core E2140 1.6 GHz	SS30S1CA	all version
Pentium Dual-Core	Intel Pentium Dual-Core E2160 1.8 GHz	SS30S1CA	all version
Pentium Dual-Core	Intel Pentium Dual-Core E2200 2.2 GHz	SS30S1CA	all version
Pentium Dual-Core	Intel Pentium Dual-Core E2220 2.4 GHz	SS30S1CA	all version

MotherBoard's PCB version: FS30 V1.X



Shuttle®

Shuttle specializes in the design and manufacturing of robust and IoT-ready small form factor PC, industrial PC, Panel PC, Kiosk, and face recognition integrated solutions.

📍 NO. 30, Lane 76, Rui Guang Rd.
Nei-Hu Dist., Taipei, Taiwan

☎ +886 2 8792 6168

✉ web@tw.shuttle.com

About Shuttle

Company Profile

Contact US

News

Investors Relations

Privacy Policy

Legal Notices

Support

Download

FAQ

Service Center

Linux Compatibility