



























## SS51G V2

[Feature](#)
[Gallery](#)
[Specifications](#)
[SpecDownload](#)
[Download](#)
[Support List](#)

[CPU Support List](#)
[Memory Support](#)
[Graphic card](#)

## CPU Support List

Socket	Model number	BIOS	BOM
Celeron	Intel Celeron 1.70 GHz	FS51SB0L 	all version
Celeron	Intel Celeron 1.80 GHz	FS51SB0L 	all version
Celeron	Intel Celeron 2.00 GHz	FS51SB0L 	all version
Celeron	Intel Celeron 2.10 GHz	FS51SB0L 	all version
Celeron	Intel Celeron 2.20 GHz	FS51SB0L 	all version
Celeron	Intel Celeron 2.30 GHz	FS51SB0L 	all version
Celeron	Intel Celeron 2.40 GHz	FS51SB0L 	all version
Celeron	Intel Celeron 2.50 GHz	FS51SB0L 	all version
Celeron	Intel Celeron 2.60 GHz	FS51SB0L 	all version
Celeron	Intel Celeron 2.70 GHz	FS51SB0L 	all version
Celeron	Intel Celeron 2.80 GHz	FS51SB0L 	all version
Pentium 4	Intel Pentium 4 1.50 GHz	FS51SB0L 	all version
Pentium 4	Intel Pentium 4 1.60 GHz	FS51SB0L 	all version
Pentium 4	Intel Pentium 4 1.70 GHz	FS51SB0L 	all version
Pentium 4	Intel Pentium 4 1.80 GHz	FS51SB0L 	all version
Pentium 4	Intel Pentium 4 1.90 GHz	FS51SB0L 	all version
Pentium 4	Intel Pentium 4 2.00 GHz	FS51SB0L 	all version
Pentium 4	Intel Pentium 4 2.20 GHz	FS51SB0L 	all version
Pentium 4	Intel Pentium 4 2.26 GHz	FS51SB0L 	all version
Pentium 4	Intel Pentium 4 2.40 GHz	FS51SB0L 	all version
Pentium 4	Intel Pentium 4 2.40A GHz	FS51SB0L 	all version
Pentium 4	Intel Pentium 4 2.50 GHz	FS51SB0L 	all version
Pentium 4	Intel Pentium 4 2.53 GHz	FS51SB0L 	all version
Pentium 4	Intel Pentium 4 2.66 GHz	FS51SB0L 	all version
Pentium 4	Intel Pentium 4 2.80A GHz	FS51SB0L 	all version
Pentium 4	Intel Pentium 4 3.06 GHz *	FS51SB0L 	all version

MotherBoard's PCB version: FS51V2.x

Remarks:

Remark:

1. CPU internal core bus speed runs at 400/533MHz. 2. \*SS51G does not support Intel CPU with Hyper-Threading Technology, but there is no problem running such CPU. 3. Prescott/Celeron D processor are not supported.



## Shuttle

Shuttle specializes in the design and manufacturing of robust and IoT-ready small form factor PC, industrial PC, Panel PC, Kiosk, and face recognition integrated solutions.

 NO. 30, Lane 76, Rui Guang Rd.  
 Nei-Hu Dist., Taipei, Taiwan

 +886 2 8792 6168

 web@tw.shuttle.com

## About Shuttle

[Company Profile](#)

[Contact US](#)

[News](#)

[Investors Relations](#)

[Privacy Policy](#)

[Legal Notices](#)

## Support

[Download](#)

[FAQ](#)

[Service Center](#)

[Linux Compatibility](#)