



































ST61G4

[Feature](#)
[Gallery](#)
[Specifications](#)
[SpecDownload](#)
[Download](#)
[FAQ](#)
[Support List](#)

[CPU Support List](#)
[Memory Support](#)
[Graphic card](#)
[Accessory Support](#)

CPU Support List

Socket	Model number	BIOS	BOM
Celeron	Intel Celeron 2.00 GHz	FT61S02D 	all version
Celeron	Intel Celeron 2.10 GHz	FT61S02D 	all version
Celeron	Intel Celeron 2.20 GHz	FT61S02D 	all version
Celeron	Intel Celeron 2.30 GHz	FT61S02D 	all version
Celeron	Intel Celeron 2.40 GHz	FT61S02D 	all version
Celeron	Intel Celeron 2.50 GHz	FT61S02D 	all version
Celeron	Intel Celeron 2.60 GHz	FT61S02D 	all version
Celeron	Intel Celeron 2.80 GHz	FT61S02D 	all version
Celeron D	Intel Celeron D 320 2.40 GHz	FT61S02D 	all version
Celeron D	Intel Celeron D 325 2.53 GHz	FT61S02D 	all version
Celeron D	Intel Celeron D 330 2.66 GHz	FT61S02D 	all version
Celeron D	Intel Celeron D 335 2.80 GHz	FT61S02D 	all version
Celeron D	Intel Celeron D 340 2.93 GHz	FT61S02D 	all version
Celeron D	Intel Celeron D 345 3.06 GHz	FT61S02D 	all version
Pentium 4	Intel Pentium 4 1.80 GHz	FT61S02D 	all version
Pentium 4	Intel Pentium 4 2.00 GHz	FT61S02D 	all version
Pentium 4	Intel Pentium 4 2.20 GHz	FT61S02D 	all version
Pentium 4	Intel Pentium 4 2.26 GHz	FT61S02D 	all version
Pentium 4	Intel Pentium 4 2.40 GHz	FT61S02D 	all version
Pentium 4	Intel Pentium 4 2.40A GHz	FT61S02D 	all version
Pentium 4	Intel Pentium 4 2.50 GHz	FT61S02D 	all version
Pentium 4	Intel Pentium 4 2.53 GHz	FT61S02D 	all version
Pentium 4	Intel Pentium 4 2.60 GHz	FT61S02D 	all version
Pentium 4	Intel Pentium 4 2.66 GHz	FT61S02D 	all version
Pentium 4	Intel Pentium 4 2.80 GHz	FT61S02D 	all version
Pentium 4	Intel Pentium 4 2.80A GHz	FT61S02D 	all version
Pentium 4	Intel Pentium 4 2.80E GHz	FT61S02D 	all version
Pentium 4	Intel Pentium 4 3.00E GHz	FT61S02D 	BOM 14
Pentium 4	Intel Pentium 4 3.06 GHz	FT61S02D 	BOM 14
Pentium 4	Intel Pentium 4 3.20 GHz	FT61S02D 	all version
Pentium 4	Intel Pentium 4 3.20E GHz	FT61S02D 	BOM 14
Pentium 4	Intel Pentium 4 3.40 GHz	FT61S02D 	all version
Pentium 4	Intel Pentium 4 3.40E GHz	FT61S02D 	BOM 14
Pentium EE	Intel Pentium 4 Extreme Edition 3.00 GHz	FT61S02D 	BOM 14

MotherBoard's PCB version: FT61V1.0

Remarks:

1. CPU internal core bus speed runs at 400/533/800MHz. 2. Willamette core CPUs is not supported. 3. ST61G4 BOM 13 or lower can only support Prescott core CPU up to and including 2.8GHz CPU.



Shuttle®

Shuttle specializes in the design and manufacturing of robust and IoT-ready small form factor PC, industrial PC, Panel PC, Kiosk, and face recognition integrated solutions.

 NO. 30, Lane 76, Rui Guang Rd.
Nei-Hu Dist., Taipei, Taiwan

 +886 2 8792 6168

 web@tw.shuttle.com

About Shuttle

[Company Profile](#)

[Contact US](#)

[News](#)

[Investors Relations](#)

[Privacy Policy](#)

[Legal Notices](#)

Support

[Download](#)

[FAQ](#)

[Service Center](#)

[Linux Compatibility](#)