

Media centre solution with Blu-ray drive

Grey and big is out. Shuttle XPCs are in. They are not only surpass all standards of Home-Entertainment, but also look elegant and stylish. Best performance and outstanding optics make the Shuttle XPC a real eyecatcher. It can be used as a digital video recorder, DVD-player and music center without any problems. Store and archive your recordings long-term via the integrated DVD-writer. Even play or save your personal videos on the Shuttle XPC using the Firewire connector. The sheer magnitude of uses means the Shuttle XPC grows to become the pivot of digital life - as a perfect Media Center. Due to its small dimensions and individual arrangements, the Shuttle XPC blends ideally into every surrounding bringing computing into the living room era. The Shuttle XPC - YOUR Media Center for the living room!

Shuttle XPC G5 6801M



| Feature Highlight | |
|-------------------------------|---|
| Category | <ul style="list-style-type: none"> Media Center |
| Shuttle XPC | <ul style="list-style-type: none"> Based on Shuttle XPC Barebone SN68G2 plus VFD Media Display (PF27) |
| OS | <ul style="list-style-type: none"> Microsoft Windows Vista (Home Premium or Ultimate) |
| Processor | <ul style="list-style-type: none"> AMD Athlon 64 X2 or similar |
| Memory | <ul style="list-style-type: none"> DDR2-667/800, Dual Channel up to 4 GB |
| Graphics | <ul style="list-style-type: none"> PCIe x16 Grafikkarte ATI or NVIDIA |
| TV Tuner | <ul style="list-style-type: none"> One or two TV tuners (analog, DVB-T or hybrid) |
| VFD display | <ul style="list-style-type: none"> VFD Media Display and remote control |
| Audio | <ul style="list-style-type: none"> 8-ch Audio with optional SPDIF in/out |
| LAN | <ul style="list-style-type: none"> Gigabit Ethernet LAN (1000 Mbit/s) |
| Drives | <ul style="list-style-type: none"> Blu-ray drive (optional HD-DVD) Serial ATA II hard disk |
| Warranty | <ul style="list-style-type: none"> 24 months Pick-up and Return Service |
| Further configuration options | <ul style="list-style-type: none"> It is possible to modify certain components of this configuration. Please refer to the "Shuttle Systems Configurator" on Shuttle's website sys.eu.shuttle.com |

Pictures are illustration only.

Shuttle XPC G5 6801M Specifications (configurable)

| | |
|-----------------------------|---|
| <i>Range of application</i> | Media Center |
| <i>Basis</i> | System based on: Shuttle XPC Barebone SN68SG2 with PF27 (Mirror front plate with VFD Media Display) |
| <i>Operating system</i> | Microsoft Windows Vista Home Premium / Ultimate 9 languages available: German, English, French, Dutch, Italian, Spanish, Swedish, Finnish, Danish |
| <i>Software</i> | CyberLink PowerDVD Ultra (2 channel or 7.1 channel) |
| <i>Chassis</i> | G5-type aluminum chassis, color: black stealthed drive doors, mirroring front panel Dimensions: 31 x 20 x 18.5 cm (LWH) |
| <i>VFD Media Display</i> | Integrated Versatile front-panel display Displays the information you need right on the front of your XPC Compliant to Windows Media Center With integrated infrared receiver for the MCE remote control |
| <i>Remote Control</i> | Infrared remote control, compliant to Windows Media Center |
| <i>Processor</i> | With AMD Processor in the AM2 socket: AMD Athlon 64 X2 with 1 GHz HyperTransport Technology x16 Up/Down |
| <i>Silent X Cooling</i> | Shuttle I.C.E. (Integrated Cooling Engine) advanced I.C.E. Heatpipe technology, linear controlled 92mm fan SilentX cooling and noise reduction technology with Active Airflow |
| <i>Chipset</i> | NVIDIA Single chip solution NVIDIA GeForce 7025 and nForce 630a (Codename: MCP 68S) |
| <i>Hard disk</i> | Serial ATA II hard disk up to 1000GB, 3.5" format |
| <i>Optical drive</i> | Blue-ray drive, optional with HD-DVD functionality, combo or writer |
| <i>Card reader</i> | 25-in-1 Card Reader, 3.5" device, internal USB 2.0 port |
| <i>Memory</i> | DDR2-667/800 SDRAM memory 2 x 240 pin slots, supports Dual Channel up to a total size of 4 GB, max. 2 GB per DIMM |

| | |
|---------------------------------------|---|
| <p><i>PCIe x16 Graphics card</i></p> | <p>PCI Express x16 graphics card from NVIDIA or ATI Video outputs: DVI (digital), D-sub VGA (analog) and S-Video (TV)</p> |
| <p><i>TV Tuner Card</i></p> | <p>Analog TV card including Hardware MPEG2 encoder and FM Tuner Optional DVB-T tuner card (without FM Tuner) Or dual tuner cards (2x Analog or 2x DVB-T) Or hybrid card (including Analog and DVB-T Tuner) Compliant to Windows Media Center</p> |
| <p><i>8ch Audio</i></p> | <p>7.1 channel High Definition Audio, Realtek ALC888 codec High-performance 103dB SNR quality Playback sampling rates up to 96 kHz Analog: line-out (8-ch), line-in, microphone Digital (optional): optical S/PDIF input/output (Accessory PC17)</p> |
| <p><i>Giga LAN</i></p> | <p>Marvell 88E1116 Ethernet network controller (Gigabit PNY) PCI Express x1 interface Supports 100 / 1.000 MBit/s operation Supports Wake-on-LAN (WOL)</p> |
| <p><i>Firewire</i></p> | <p>Firewire controller TI TSB43AB22A IEEE1394 OHCI V1.0 compliant with 2 Firewire connectors (front and rear) supports 400Mb/s, 200Mb/s, 100Mb/s data transfer rate</p> |
| <p><i>Front-panel I/O</i></p> | <p>Microphone Headphone (Line-out) 2x USB 2.0 Firewire (Mini 4 pin connector) Power button Reset button Power indicator (blue LED) HDD indicator (orange LED)</p> |
| <p><i>Back-panel I/O</i></p> | <p>DVI (digital video) with DVI-to-HDMI adapter Sub-D VGA (analog video) S-Video (TV output) 4x USB 2.0 GigaBit LAN (RJ45) IEEE1394 Firewire (6 pin) 2x External Serial ATA (eSATA) 8-ch Audio line out (2x rear/front, bass/center, surround/back) Optical S/PDIF input/output (digital audio, PC17) Audio Line-in CMOS button</p> |
| <p><i>Optional Back-panel I/O</i></p> | <p>Wireless LAN module (PN18) Parallel port (PC8)</p> |

© 2006 by Shuttle Computer Handels GmbH (Germany). All information subject to change without notice. Pictures for illustration purposes only.

| | |
|---|--|
| <p><i>Power supply</i></p> | <p>250 Watt mini power supply unit Input voltage range: 100~240V Connectors: 20-pin ATX, 4-pin ATX12V Dimensions: 190 (L) x 82 (W) x 43 (H) mm EMI certified: FCC, CE, BSMI, CCC Safety certified: UL, TÜV, CB, BSMI, CCC Active PFC (Power Factor Correction)</p> |
| <p><i>Warranty</i></p> | <p>24 Months Pick-Up-And-Return Service</p> |
| <p><i>Further configuration options</i></p> | <p>It is possible to modify certain components of this basic configuration. Please refer to the "Shuttle Systems Configurator" on Shuttle's website http://sys.eu.shuttle.com</p> |