

### Smart budget solution for simple tasks

The Shuttle K450V PC system is a great choice for basic computing needs such as office applications and web surfing in the business or home segment. It is a small and stylish PC platform with low power consumption that seamlessly integrates into a network using its Ethernet or an optional WLAN interface. This affordable entry-level platform with preinstalled OpenSUSE Linux operating system targets SME, corporate, public and educational institutions. Easily set up an ideal second home PC to manage any simple everyday applications in a snap while banking on Shuttle's high reliability.



**Shuttle**  
**K450V**



### Feature Highlight

<b>K chassis</b>	<ul style="list-style-type: none"> <li>• Black chassis with aluminum cover</li> <li>• Dimensions: 28 x 19 x 17 cm (L/W/H)</li> <li>• Bays: 2x 3.5" (internal)</li> </ul>
<b>OS</b>	<ul style="list-style-type: none"> <li>• OpenSUSE Linux</li> </ul>
<b>Chipset</b>	<ul style="list-style-type: none"> <li>• Intel 945GC + ICH7</li> <li>• Integrated GMA950 graphics, VGA out</li> </ul>
<b>CPU</b>	<ul style="list-style-type: none"> <li>• Socket 775</li> <li>• Core 2 Duo E6xxx / E4xxx, Pentium Dual-Core 2xxx and Celeron 4xx (max. 65W)</li> <li>• Up to 1333 MHz FSB, 65nm or 45nm</li> </ul>
<b>Slots</b>	<ul style="list-style-type: none"> <li>• 1x PCI 32 Bit</li> </ul>
<b>Memory</b>	<ul style="list-style-type: none"> <li>• Up to 2GB DDR2-533/667</li> </ul>
<b>Drive</b>	<ul style="list-style-type: none"> <li>• SATA II hard disk (80GB ~ 1000GB)</li> </ul>
<b>Other</b>	<ul style="list-style-type: none"> <li>• 5.1 HD audio</li> <li>• 4x USB 2.0</li> <li>• Gigabit LAN</li> <li>• Optional WLAN adapter</li> </ul>
<b>Power supply</b>	<ul style="list-style-type: none"> <li>• 100 Watt Flex-ATX power supply</li> </ul>
<b>Application</b>	<ul style="list-style-type: none"> <li>• Business</li> </ul>

Images for illustration purposes only.

## Shuttle **K450V** Specifications

<i>Range of application</i>	Recommended for business use
<i>Basis</i>	System based on: the Shuttle K-Series Barebone K45
<i>Operating system</i>	OpenSUSE Linux, powered by Novell
<i>Chassis</i>	K-type aluminum chassis, color: black dimensions: 28 x 19 x 17 cm (LWH)
<i>Processor</i>	Socket 775 with Intel Celeron 430 processor (1.8GHz) or higher e.g. Celeron 4xx, Pentium Dual-Core E2xxx, Core 2 Duo E4xxx/E6xxx Supports up to 1333 MHz front side bus, 65/45nm technology and maximum 65W TDP (power consumption)
<i>Cooling technology</i>	Big 92mm chassis fan at the rear side and Intel-boxed processor cooler Temperature-controlled RPM fan speed (Smart fan technology)
<i>Chipset</i>	Intel® 945GC Express Chipset (MCH, Northbridge) + ICH7 (Southbridge)
<i>Hard disk</i>	3.5" Serial ATA 300 hard disk (from 80GB up to 1000GB)
<i>Memory</i>	One or two memory modules DDR2-533/667 (240 pins) Can be configured with 512MB or up to 2 GB total capacity.
<i>Integrated Graphics</i>	Intel Graphics Media Accelerator 950 (GMA950) with PCI-E x1 improved bandwidth, features 333MHz graphics core DX8/DX9 support and enhanced 3D performance Dynamic Video Memory Technology (DVMT) 3.0 Shared Memory max. 224MB Analog 15 pin Sub-D VGA video out connector
<i>Audio</i>	Audio Realtek® ALC 662 6-channel High-Definition Audio Three analog audio connectors (3.5mm) at the Back-Panel: 1) Front Line out (head phone) 2) Rear Surround line-out (shared with microphone input) 3) Center line-out (shared with Line in)
<i>LAN controller</i>	Gigabit Ethernet network controller (Marvell 8056) Supports 10/100/1000 MBit/s operation RJ45 back panel connector Supports Wake-on-LAN function and PXE (Preboot Execution Environment)

<i>Front panel buttons &amp; LEDs</i>	<p>Power button                  Power indicator (LED)                  HDD indicator (LED)</p>
<i>Back panel connectors</i>	<p>D-sub VGA Video out                  4x USB 2.0                  RJ45 LAN connector                  PS/2 keyboard connector                  PS/2 mouse connector                  Serial COM port                  Parallel port                  Audio Front Line out (head phone)                  Audio Rear Surround line-out (shared with microphone input)                  Audio Center line-out (shared with Line in)                  Optional Wireless LAN module (PN20)</p>
<i>Slots</i>	<p>1x PCI (32 bit)</p>
<i>Power supply</i>	<p>100 Watt Flex ATX power supply unit                  Input voltage range: 100~240V AC, 47~63 Hz                  Active PFC (Power Factor Correction)                  EMI Certified: FCC, CE, BSMI                  Safety Certified: UL, TÜV, CB                  Power plug region specific, 40 mm cooling fan sensor control</p>
<i>Further configuration options</i>	<p>It is possible to modify certain components of this system.                  Please refer to the "Shuttle Systems Configurator".</p>
<i>Warranty</i>	<p>24 Months</p>

Connectors and Components

**Front-Panel**

- F1 Power Switch
- F2 Power LED
- F3 HDD LED



**Back-Panel**

- B1 Optional WLAN
- B2 AC Power Socket
- B3 PS/2 Mouse Port
- B4 PS/2 Keyboard Port
- B5 COM Port
- B6 Parallel Port
- B7 VGA Port
- B8 USB Port
- B9 LAN Port
- B10 MIC-In Port
- B11 Line-Out Port
- B12 Line-In Port
- B13 PCI Slot
- B14 Rear Fan

