

Fanless Slim PC with Intel Atom Dual Core processor

The Shuttle Slim PC XS36V-703 is an extremely slim and ergonomic Mini PC that works highly energy-efficiently. With a power consumption that is barely worth mentioning, and because of its completely fanless case layout, it is virtually maintenance-free and noiseless. This PC platform is powered by an Intel Atom D2700 dual-core processor (2x 2.13 GHz) with integrated GMA 3650 graphics, 2GB DDR3 memory, 160GB hard disk, WLAN (n) and card reader. The operating system not included. It sports an array of connectors too which include HDMI 1.3, DVI-D, D-Sub (VGA), 5x USB, Gigabit-LAN, audio ports and two RS232 COM ports for business and vertical Markets.

Slim PC System **XS36V-703**



Feature Highlights

Chassis	<ul style="list-style-type: none"> Slim 1.1 litre chassis Dimensions: 20 x 16 x 3.6 cm Hole for the Kensington Lock Optional VESA mount (PV03)
Operating system	<ul style="list-style-type: none"> Without operating system Compatible with Windows 7 (32 bit)
CPU	<ul style="list-style-type: none"> Intel Atom D2700 Dual Core (2.13GHz)
Chipset	<ul style="list-style-type: none"> Intel NM10 Express Chipset
Graphics	<ul style="list-style-type: none"> Integrated Intel GMA3650 Graphics Shared Memory: max. 384MB DVMT
Memory	<ul style="list-style-type: none"> 2 GB DDR3 SO-DIMM memory
Storage	<ul style="list-style-type: none"> 160 GB SATA hard disk (2.5") Built in SD card reader
Connectors and WLAN	<ul style="list-style-type: none"> HDMI v1.3 (supports digital audio) DVI-D D-Sub VGA 5x USB 2.0 (1x front, 4x rear) Microphone input Headphones output (Line-out) Gigabit-LAN 2x RS232 COM-Ports WLAN 802.11 b/g/n
Power supply	<ul style="list-style-type: none"> External 40W fanless power supply
Applications	<ul style="list-style-type: none"> Basic and Home-Media

Images are only for illustration purposes.



Shuttle order no. PEC-XS36V001



Shuttle Slim PC XS36V-703 - Product Features



Point of sales with Shuttle XS36V-703




Ideal for professional applications

Designed as a space-saver, this sleek 1.3 litre nettop PC only measures 3.3 cm in width. It maximizes space whether it is placed upright using its stand or affixed to the back of a display with the optional VESA mounting kit. Due to its small size and flexible design, this practical nettop offers exceptional functionality. It is well-suited for professional applications like digital signage, POS system, POI terminals, control PC or office PC (e.g. thin client). Thanks to the serial ports you can connect appropriate POS displays, cash register drawer or digital sensors. It is also possible to add an internal USB stick as a low cost storage device.

Fanless and quiet

The Shuttle Slim PC XS36V-703 comes totally fanless making it perfect to be used in noise-sensitive environments such as living rooms, hospitals, libraries etc. As an additional benefit, fanless cases rarely gather dust on the inside and stay cleaner than others. So it's not only quiet and low in energy use, but also dust-free and virtually maintenance free.



The Atom processor integrates the graphics controller

Shuttle XS36V-703 is equipped with Intel's Atom D2700 processor (2,13GHz, codenamed Cedarview). It comes with both the memory controller and graphics core on-die which helps to keep heat dissipation and memory latency low. The CPU is connected to the Southbridge NM10, codenamed Tiger Point.

Dual Core. Do more.

Shuttle always uses the dual-core variant of Intel's Atom processors and thus integrates the Atom D2700. This boosts the system performance significantly with particular regards to multi-threaded applications.



Highly energy-saving

The XS36V-703 barely consumes, depending on system load, about 16~25 Watts. Running the device*) 5 days a week for eight hours a day, the annual consumption would amount to less than 40kWh which would mean just 8 Euros on the power bill (20 Euro ct/kWh) - way less than a conventional desktop PC draws.

*) Based on a configuration with 2GB of memory, 160GB hard disk and Windows 7 32 bit.



Supports two displays

The integrated graphics supports multiple display support on up to two separate monitors via HDMI, DVI-D and D-Sub/VGA. This improves the capabilities and productivity of the user by allowing them to spread multiple windows over two monitors and view them simultaneously.



SD card reader

The built-in SD card reader at the front side makes it easy to transfer files from your camera so you can share videos and photos on your XS36V-703 with ease.



Kensington Lock

This is a small, metal-reinforced hole as part of an anti-theft system. As known from notebooks, this Mini-PC can also be safely locked by tying it to a solid object.

(The lock-and-cable apparatus is not included.)



Tiny power adapter

The external 40W power adapter is virtually noiseless and can easily be hidden behind the desk thanks to its tiny dimensions.

Dimensions: 89.5 x 37 x 26.5 mm (LWH) = 88ml



Two serial RS-232 ports (COM)

XS36V-703 features two serial RS232 COM ports in the front panel.

Today, many consumer PCs do no longer have this legacy port, since that interface has been superseded by USB. Still, they are commonly used for applications of industrial automation systems, scientific analysis, and POS systems.



Optional VESA mount (Accessory PV03)

Its optional VESA75/100 wallmount allows it to be installed on to walls or just affixed on the rear side of a monitor which is particularly interesting for the industry segment, company buildings and public institutions.



24/7 nonstop operation

Shuttle XS36V-703 is officially approved for 24/7 permanent operation. Thanks to its low power consumption and completely passively cooling, this PC runs highly reliable making it perfectly suitable for digital signage and POI/POS applications.

Conditions for permanent use:

- Ambient temperature while under load: 5-35°C
- Air humidity while under load: 10-90% (not condensing)
- Free circulation of air amongst the PC must be guaranteed
- Ventilation holes must be clear
- If a hard disk is installed, this must also be approved for permanent operation by its manufacturer (max. one hard disk)



Note on operating position

Please make sure the system is always placed upright using either its stand or the optional VESA mount (PV03). Ventilation holes must not be blocked to ensure sufficient cooling.

Shuttle Slim PC XS36V-703 Specifications

<i>Fanless and silent</i>	<p>Passive cooling, no fan noise at all Perfect to be used in noise-sensitive environments Fanless, dust-free and thus virtually maintenance-free</p>
<i>Low current</i>	<p>Power consumption: ca. 16W (idle mode) and ca. 25W (full load)</p>
<i>Chassis</i>	<p>Dimensions without Stand: 20 x 16 x 3.6 cm (DxHxW) = 1.15 litres Weight: 1.6 kg net, 2.3 kg gross Hole for the Kensington Lock at the back panel Optional accessory: 75mm and 100mm VESA mounting kit (PV03)</p>
<i>Operation System</i>	<p>This system comes without operating system. It is compatible with Windows 7 (32 bit)</p>
<i>Processor</i>	<p>Intel Dual Core Atom processor D2700 (Codename: Cedarview) Intel Hyper-Threading technology: 2-threads per core 32 nm manufacturing process, FCBGA559 package Intel 64 architecture, Core clock: 2.13 GHz L2 Cache: 1024kB , TDP: max. 10W Supports SSE2, SSE3, SSSE3, Execute Disable Bit Integrated North Bridge with controller for memory and graphics</p>
<i>Cooling</i>	<p>Passive, completely fanless cooling through convective heat transfer Warning: Please make sure the system is always placed upright using either its stand or the optional VESA mount. Ventilation holes must not be blocked to ensure sufficient cooling.</p>
<i>Chipset</i>	<p>Intel® NM10 Express Chipset (south bridge) Platform Controller Hub (PCH) Code name: Tiger Point</p>
<i>BIOS</i>	<p>AMI BIOS in a 8Mbit Flash ROM supports PnP, ACPI 2.0 Supports external USB flash memory card boot up Supports Power fail resume / AC power on state / always on / always off Supports Wake-on-LAN (WOL) from S3, S3, S5 ACPI states Supports Unified Extensible Firmware Interface (UEFI)</p>
<i>Memory</i>	<p>2GB DDR3 SO-DIMM memory</p>
<i>Hard disk drive or SSD</i>	<p>160 GB SATA hard disk in 6.35cm/2.5" format</p>

<p><i>Integrated Graphics</i></p>	<p>The Graphics Processing Unit (GPU) is integrated into the processor Intel GMA 3650, Graphics Base Frequency: 640 MHz Supports DirectX 9 Maximum shared memory: 8MB pre-allocated plus 384MB Video Memory Technology (DVMT) Three video outputs: HDMI v1.3, DVI-D and D-Sub (VGA) Two outputs can be used at the same time. Supports dual display in clone or extended mode. HDMI and DVI support the Intel HDCP function (High bandwidth Digital Content Protection) HDMI/DVI display resolution up to 1920x1200.</p>
<p><i>Integrated Audio</i></p>	<p>Integrated Audio IDT92HD81 Audio Codec with Azalia support Two analog audio connectors (3.5mm): 1) Line out (head phone) 2) microphone input Supports digital 7.1 HD audio via the HDMI port.</p>
<p><i>Card Reader</i></p>	<p>Integrated card reader supports SD, SDHC and SDXC memory flash cards</p>
<p><i>Wired Network</i></p>	<p>RJ45 connector supports Gigabit LAN at 10/100/1000 Mbit/sec. Network controller JMC 251 Supports Wake-on-LAN (WOL) from S3, S3, S5 ACPI states</p>
<p><i>Wireless Network</i></p>	<p>Supports IEEE 802.11b/g/n, max. 150Mbps up-/downstream Security: WPA/WPA2(-PSK), WEP 64/128bit, IEEE 802.11x/i Half size Mini-PCIe-Card</p>
<p><i>Connectors</i></p>	<p>HDMI v1.3 digital video and audio output DVI-D digital video output D-Sub/VGA analog video (15 pin) 5x USB 2.0 (1x front, 4x rear) Gigabit network (LAN, RJ45) Audio Line-out (head phone) Microphone input 2x RS232 COM ports (front panel) DC input for the external power adapter</p>
<p><i>LEDs and buttons</i></p>	<p>Power button Power LED (white) Hard disk LED (blue)</p>
<p><i>Power supply</i></p>	<p>External 40W AC/DC power adapter (fanless), 19V / 2.1A AC Input: 100~240V AC, 50~60Hz Automatic voltage adjust Dimensions: 89.5 x 37 x 26.5 mm (LWH) DC Connector: 5.5/2.5mm (outer/inner diameter)</p>

<i>24/7 nonstop operation</i>	<p>This device is approved for 24/7 permanent operation.</p> <p>Requirements:</p> <ul style="list-style-type: none"> - Free circulation of air amongst the PC must be guaranteed. - Ventilation holes must be clear. - If a hard disk is installed, this must also be approved for permanent operation by its manufacturer (max. one hard disk)
<i>Environ- mental spec.</i>	<p>Operating temperature range: 0~35°C</p> <p>Relative humidity range: 10~90% (non-condensing)</p>
<i>Certification and Compliance</i>	<p>EMI: CE, FCC, BSMI, C-Tick, CCC</p> <p>Safety: CB, BSMI, ETL</p> <p>Other compliances: RoHS, Eup Lot6</p> <p>This device is classed as a technical information equipment (ITE) in class B and is intended for use in living room and office. The CE-mark approves the conformity by the EU-guidelines:</p> <ul style="list-style-type: none"> - EMV-guideline 89/336/EWG electromagnetic tolerance - LVD-guideline 73/23/EWG use of electric devices within certain voltage-limits

Comparison: Shuttle Slim-PC XS36 Series (Barebone/System)

Model	Type	Processor	OS	Memory	HDD	Barcode
XS36V	Barebone	Intel Atom D2700	-	-	-	UPC: 811686003687
XS36V-703	System w/o OS	Intel Atom D2700	-	2 GB	160 GB	EAN: 4046047102488
XS3600BA	System with OS	Intel Atom D2700	Win 7 Prof. 32 bit	2 GB	160 GB	EAN: 4046047102471

Comparison: Shuttle Slim-PC Barebone PC XS35/XS36 Series

Model	Graphics	HDMI	DVI	D-Sub	RS232	WOL	Processor	Memory (SO-DIMM)	Other
XS35	Intel GMA3150	-	-	Yes	-	-	Intel Atom D510 (2x 1.66GHz)	Max. 2GB DDR2-800 1x SO-DIMM slot	Fast Ethernet
XS35GT	NVIDIA ION2	Yes	-	Yes	-	-		Intel Atom D525 (2x 1.80GHz)	Max. 4GB DDR3-800 1x SO-DIMM slot
XS35V2	Intel GMA3150	-	-	Yes	-	-			
XS35GT V2	NVIDIA ION2	Yes	-	Yes	-	-			
XS35GTA V2	ATI Mobility Rad. HD 5430	Yes	-	Yes	-	-	Intel Atom D2700 (2x 2.13GHz)	Max. 4GB DDR3-1066 2x SO-DIMM slots	Gigabit LAN
XS35V3	Intel GMA3650 [2]	Yes	-	Yes	-	Yes [3]			
XS35GTA V3 [1]	ATI Radeon HD 7410M	Yes	-	Yes	-	Yes [3]			
XS36	Intel GMA3650 [2]	Yes	Yes	Yes	2x	Yes [3]			

[1] **XS35GTAV3** is also called **XS35GS V3** outside EU.

[2] Intel offers sophisticated graphics driver for the integrated **Intel GMA3650** graphics only for [Windows 7 32 bit](#). Linux can be used in standard mode without video acceleration. (date April 2012)


[3] Supports Wake-on-LAN (WOL), Power fail resume (always on/off) and Resume by RTC Alarm

Shuttle Slim PC XS36V-703 – Connectors

Front Panel



Back Panel



- 1 Power button
- 2 Power LED
- 3 Hard disk LED
- 4 2x RS232 COM ports
- 5 SD card reader
- 6 Vertical stand
- 7 USB 2.0 connector

- A Microphone input
- B Head phone output (Line out)
- C Gigabit LAN connector (RJ45)
- D 4x USB 2.0 connectors
- E DVI-D connector
- F Vertical stand
- G Hole for the Kensington-Lock
- H HDMI connector
- I D-Sub/VGA connector
- J Connector for the power adapter



Warning:

Please make sure the system is always placed upright using either its stand or the optional VESA mount (PV03). Ventilation holes must not be blocked to ensure sufficient cooling.