

Panel-PC Barebone M15AL01-i5 White

Intel Core i5-1235 ULV CPU

MEDICAL-GRADE PANEL PC WITH 15.6" TOUCH-DISPLAY

This high-value Panel PC comes features a rugged Aluminium chassis with an anti-bacterial and anti-septic coating and IP65-rated front panel for superior hygiene and infection control. It is powered by an Intel Core Gen12 processor and the Full-HD display sports a projected capacitive 10-point multi-touch function. With its passive cooling the system is virtually noiseless, maintenance-free and approved for 24/7 nonstop operation. Compliant with IEC 60601-1 medical safety standards for electrical devices, this Panel PC is built for reliable operation in a wide range of healthcare environments.



Images for illustration only.



15.6" Touch Display



Anti-Septic Housing



2x 32 GB Support



NVMe SSD Support



WLAN/BT Ext. Antennas



HDMI 2.0b & VGA Port



4x USB 3.2
4x USB 2.0



Serial Port



100 x 100 mm VESA mount



Fanless



IP65 (Front)



24/7 Support

ROBUST CHASSIS

- Robust Aluminium chassis (3 mm thickness) with magnetic cover for the I/O connectors
- IP65 front panel protection
- Dimensions (WHD): 394.3 x 256.2 x 48.9 mm
- Net weight: 4.6 kg
- Fanless cooling system
- Operating temperature: 0 ~ 40 °C
- Humidity: 20 ~ 80% RH non-condensing
- Mounting holes for 100 x 100 mm VESA mount (VESA mount and stand are not included)

MEDICAL-GRADE FEATURES

- Anti-Septic coating based on an inorganic zinc compound (front panel) and epoxy/polyester resin (rear chassis)
- Medical power adapter (90 W)
- Potential equalization pin (POAG)
- Medical certificates: CE EN60601-1-2:2015+A1:2021, FCC Part 18, cTUVus(ANSI/AAMI ES60601-1:2005/A2:2021), CB(IEC 60601-1:2005/AMD2:2020)

TOUCH DISPLAY

- High quality 15.6" / 39.6cm display with 1920x1080 pixels
- Brightness: 350 cd/m2, Contrast ratio 1000:1, Viewing angle: 89° (all directions)
- Capacitive touch panel with 10-point multi-touch
- Supports two additional displays with HDMI 2.0b and VGA ports

OPERATING SYSTEM

- An operating system is not included.
- Supports Windows 10, Windows 11 and Linux (64-bit)

PROCESSOR & GRAPHICS

- Intel Core i5-1235, 2 P-Cores, 8 E-Cores, 12 MB Cache
- "Alder Lake" ULV Prozessor (Gen 12), 15 W TDP
- Integrated Intel® Iris® Xe graphics

MEMORY/STORAGE (not included)

- RAM: 2x 262-pin SO-DIMM slot supports up to 2x 32 GB DDR5-4800
- M.2-SSD card: M.2-2280/2242 M slot supports PCIe/NVMe and SATA

BACK PANEL CONNECTORS

- HDMI 2.0b
- VGA
- 4x USB 3.2 Gen 1
- 4x USB 2.0
- 2x 2.5 Gbps LAN (Intel i226LM + i226V)
- COM Port (RS232)
- Mic-in and Line-out (Realtek)
- POAG connector
- D C-input: 19V

OTHER FEATURES

- WLAN 802.11ac and BT 4.2 with two internal antennas
- Full-HD Webcam
- Two speakers (2x 2W)
- Hardware TPM v2.0

POWER SUPPLY

- External 90W/19V power adapter
- AC input 100~240V 50~60 Hz, 3-pin connector
- Optional Wide Voltage Range: 9-36V (Accessory: VOL01)



Shuttle Panel-PCs with Intel Core Gen12 Processors "Alder Lake-U"

Touch Screen	Application	Panel-PC Model	Intel Processor	UPC Bar Code	Color (front / rear)	WLAN Antennas	DC Input	Medical Features
15.6" Full-HD 350 Nits	Industrial	P15AL01-i5	Core i5-1235U	887993007885	Black / Blue	external	9-36 V	—
	Medical	M15AL01-i5	Core i5-1235U	887993007526	White / White	internal	19 V	Anti-septic coating, POAG pin, Medical power adapter
21.5" Full-HD 500 Nits	Industrial	P21AL01-i3 P21AL01-i5	Core i3-1215U Core i5-1235U	887993007366 887993007359	Black / Blue	internal	19 V	—
	Medical	M21AL01-i5	Core i5-1235U	887993007588	White / White	internal	19 V	Anti-septic coating, POAG pin, Medical power adapter


Front and Back Panel

Front panel



- 1. 15.6" Touch Panel
- 2. Full-HD Webcam

Rear View



- 3. Anti-Septic coating
- 4. Screw threads for VESA mount (100x100 mm)
- 5. Mounted back panel cover
- 6. Potential Equalization Pin (POAG) according to DIN 42801
- 7. D-Sub/VGA port
- 8. 4x USB 2.0 Type A port
- 9. Audio Line Out (Headphones output)
- 10. Microphone input
- 11. 2.5 Gbps LAN port (Intel i226V)
- 12. 2.5 Gbps LAN port (Intel i226LM)
- 13. 4x USB 3.2 Gen 1 Type A port
- 14. HDMI 2.0b graphics port
- 15. RS232 Serial COM port
- 16. DC-in connector for power adapter
- 17. Power Button
- 18. Perforation (reserved)
- 19. Second Power Button

Back Panel



SPECIAL FEATURES



Reliable nonstop operation

The Shuttle Panel PC M15AL01-i5 is officially approved for 24/7 permanent operation at an ambient temperature of up to 40 °C. Thanks to its low power consumption and completely passive cooling, this PC runs highly reliably and is virtually noiseless.




15.6" Full-HD Touch Screen

This Panel PC has a high-grade 15.6" (39.6 cm) Full-HD display with high brightness (350 cd/qm) and low viewing angle dependence ($\pm 85^\circ$). The capacitive multitouch screen can also be operated with gloves and allows precise input with two or more fingers at the same time.



Anti-Septic Coating

The housing of this Panel PC comes with an anti-bacterial and anti-septic coating based on an inorganic zinc compound as antimicrobial substance to reduce the possibility of infection or sepsis through microorganisms like bacteria.



Robust Aluminium Chassis

Rear chassis and middle frame are completely made of high-grade Aluminium of 3 mm thickness.



Protection Class IP65

The front panel is dust-protected and protected from splashing of water according to IP protection class 65. Consequently, this All-in-One PC can be used for those indoor applications, where the touchscreen may be exposed to humidity and splashing of water. This is particularly welcome in restaurants, laboratories, production or other places.



Triple Display Support

In addition to the built-in display two more independent Full-HD displays can be connected via HDMI 2.0b and VGA.



VESA Mounting

The Shuttle Panel PC M15AL01-i5 has four threaded holes for mounting a 100 x 100 mm VESA mount. For example, a suitable stand, VESA arm or wall mount can be used to mount the Panel PC.

Note: VESA mount and stand are not included in the scope of delivery.



Optional Stand „POV21“

A stand is not included in the scope of delivery. With "POV21", Shuttle offers a suitable, robust stand made of high-quality aluminum alloy. Optionally, two devices can also be mounted on this stand (e.g. for a Panel PC and an additional display).



Optimized cable management

The connections on the back panel are facing down and hidden by a cover. The cover snaps in magnetically and is also fixed with screws.

Through a small opening the cables are led away from the PC in an orderly fashion. This leads to an effective cable management making for a clean, tidy appearance.



Hidden Power Button

Since the primary power button is not accessible when the cover is on, there is also a second power button hidden on the back. You can also enable the "Restore on AC Power Loss" option in the BIOS so that it always starts immediately once voltage is applied.



Dual Intel 2.5 Gbps Network

The Shuttle Panel PC M15AL01-i5 supports Dual 2.5 Gbps LAN with Intel network adapters, which are known for their excellent performance and driver compatibility and therefore are the preferred choice in professional environments.



Potential equalization







The Shuttle Panel PC M15AL01-i5 features a potential equalization pin (POAG) according to DIN 42801 in order to connect the Panel PC with a suitable potential equalization terminal, that can be required in medical environments, for example.











Other connection options

The backpanel has two sections, which can be assigned with other connectors, including HDMI, DVI, VGA, 4x USB and COM (RS232).

Comparison with the previous model

MODEL	M15AL01-i5 White (New)	P15WL01-i5 White
Medical-grade Features	Anti-Septic coating Medical power adapter Potential equalization pin (POAG) Medical certificates	—
Processor	Intel Core i5-1235U Intel Gen. 12 "Alder Lake-U", TDP= 15W, Intel 7 (10 nm) Technology	Intel Core i5-8365UE Intel Gen. 8 "Whiskey Lake-U", TDP= 15W, 14 nm Technology
RAM memory support	2x SO DIMM, 262 pins max. 2x 32 GB DDR5-4800 (or higher)	2x SO DIMM, 260 pins max. 2x 32 GB DDR4-2400 (or higher)
M.2-2280 Slot	M.2-2280M slot for M.2 SSD cards Supports M.2 SSD cards with 80 and 42 mm in length Supports NVMe/PCIe Gen4 X4 and SATA	M.2-2280M slot for M.2 SSD cards Supports M.2 SSD cards with 80 and 60 mm in length Supports NVMe/PCIe Gen3 X4 and SATA
15.6" Display	Resolution 1920 x 1080 Brightness: 350 cd/qm (nits) Viewing angle: 89° all directions	Resolution 1920 x 1080 Brightness: 350 cd/qm (nits) Viewing angle: 89° all directions
Intel vPro/AMT	No	vPro/AMT is supported
TPM	Hardware TPM 2.0 module (Infineon SLB9670VQ2)	Hardware TPM 2.0 module (Infineon SLB9670VQ2)
Dual LAN	2x Intel LAN with 2.5 Gbps (Intel i226V and i226LM)	2x Intel LAN with 1 Gbps (Intel i211 and i219LM)
WLAN	Realtek RTL8821CE, Wi-Fi 5 (WLAN-ac) Two internal antennas	Realtek RTL8821CE, Wi-Fi 5 (WLAN-ac) Two external antennas
Grafik Ports	HDMI 2.0b VGA	HDMI 1.4b VGA
USB Ports	4x USB 3.2 Gen1 (5 Gbps) 4x USB 2.0	4x USB 3.2 Gen1 (5 Gbps) 4x USB 2.0
COM Ports	1x Serial COM port (RS232)	1x Serial COM port (RS232)
Front View		
Rear View		
I/O Ports		

Shuttle Panel-PCs with Intel Gen12 Prozessor

Display Size	15.6" Display		21.5" Display	
Model	P15AL01-i5	M15AL01-i5	P21AL01-i3/i5	M21AL01-i5
Application	Industrial Panel-PC	Medical Panel-PC	Industrial Panel-PC	Medical Panel-PC
Chassis Color	Front: black Back: dark blue	Front: white Back: white	Front: black Back: dark blue	Front: white Back: white
Medical Coating	—	Anti-Septic Coating (front and rear)	—	Anti-Septic Coating (front and rear)
Processor Options	Intel Core i5-1235U	Intel Core i5-1235U	Intel Core i3-1215U or Intel Core i5-1235U	Intel Core i5-1235U
Display Features	Resolution: 1920 x 1080 Brightness: 350 nits 10-point capacitive touch	Resolution: 1920 x 1080 Brightness: 350 nits 10-point capacitive touch	Resolution: 1920 x 1080 Brightness: 500 nits 10-point capacitive touch	Resolution: 1920 x 1080 Brightness: 500 nits 10-point capacitive touch
I/O Ports	HDMI 2.0b, VGA 4x USB 3.2, 4x USB 2.0 2x Intel LAN (2.5G), 2x Audio, 1x COM	HDMI 2.0b, VGA 4x USB 3.2, 4x USB 2.0 2x Intel LAN (2.5G), 2x Audio, 1x COM	HDMI 2.0b, VGA 4x USB 3.2, 4x USB 2.0 2x Intel LAN (2.5G), 2x Audio, 2x COM	HDMI 2.0b, VGA 4x USB 3.2, 4x USB 2.0 2x Intel LAN (2.5G), 2x Audio, 2x COM
POAG *)	—	POAG connector with cable	—	POAG connector with cable
M.2-Slot for SSD	Supports M.2-2280 SSD card PCIe Gen4 x4 (NVMe) / SATA	Supports M.2-2280 SSD card PCIe Gen4 x4 (NVMe) / SATA	Supports M.2-2280 SSD card PCIe Gen4 x4 (NVMe) / SATA	Supports M.2-2280 SSD card PCIe Gen4 x4 (NVMe) / SATA
2.5" Bay for SSD	—	—	Supports 2.5" SSD (SATA)	Supports 2.5" SSD (SATA)
WLAN Antenna	External Antennas	Internal Antennas	Internal Antennas	Internal Antennas
Power Adapter	Standard Power Adap. 90W IEC 62368-1 / 60950-1	Medical Power Adapter 90W IEC 60601-1 / EN55011	Standard Power Adap. 90W IEC 62368-1 / 60950-1	Medical Power Adapter 90W IEC 60601-1 / EN55011
DC-Input **)	DC-Input supports 9-36V	DC-Input supports 19V	DC-Input supports 19V	DC-Input supports 19V
Front View				
Rear View				

*) **POAG:** Shuttle Medical Panel-PCs come with an **Potential Equalization Pin (POAG)** in order to connect the PC with a potential equalization terminal.

) **the DC-Input normally supports 19V input voltage only. However, an optional voltage regulator module VOL01 can be added to support an extended voltage range of 9...36V. Among the Panel PCs listed above, only the P15AL01-i5 model is already equipped with VOL01 as standard.

SHUTTLE Panel PC M15AL01-i5 — SPECIFICATIONS

FANLESS AND SILENT	<p>Passive heatpipe cooling, absolutely no fan noise</p> <p>Perfect for noise-sensitive environments</p> <p>Fanless, dust-free and thus virtually maintenance-free</p>
24/7 NONSTOP OPERATION	<p>This device is approved for 24/7 permanent operation.</p> <p>Requirements: free circulation of air amongst the PC must be guaranteed.</p>
IP65 PROTECTED	<p>The front panel is protected from dust and jets of water according to protection class IP65.</p>
CHASSIS	<p>Anti-Septic coating based on an inorganic zinc compound (front panel) and epoxy/polyester resin (rear chassis)</p> <p>Robust chassis with cover for the I/O connectors</p> <p>Rear/cable cover and middle frame are all made of Aluminium</p> <p>Rear cover chassis thickness: 3.0 mm</p> <p>Colour: White</p> <p>Dimensions: 394.3 x 256.2 x 48.9 mm (W x H x D)</p> <p>100x100 mm VESA mountable (4x M4x6L screws required)</p> <p>VESA mount and stand are not included in the scope of delivery.</p> <p>Net weight: 4.6 kg</p>
OPERATING SYSTEM	<p>This system comes without operating system. It is compatible with:</p> <ul style="list-style-type: none"> - Windows 10 (64-bit) - Windows 11 (64-bit) - please enable TPM function - Linux (64-bit)
TOUCHSCREEN	<p>Touchscreen function supports fingertip input</p> <p>Projected capacitive touch panel with 10-point multi-touch</p> <p>Supports input with gloves (PVC, cotton, cotton/linen)</p> <p>Stylus pen not supported</p>
DISPLAY (39.6 cm / 15.6")	<p>39.6 cm / 15.6" LC display</p> <p>Type: a-Si TFT-LCD</p> <p>Ratio: 16:9 wide-screen panel</p> <p>Native resolution: 1920 x 1080 = 2 Megapixel (Full HD / 1080p)</p> <p>Viewing angle (left/right/up/down): 89°</p> <p>Brightness: 350 cd/sqm or nits (typ.)</p> <p>Contrast: 1000:1 (typ.)</p> <p>Signal Interface: eDP 30 pins (2 lanes)</p>
PROCESSOR	<p>Model: Intel Core i5-1235U (ULV)</p> <p>12th Generation Intel Core, code name "Alder Lake-U"</p> <p>System-on-a-chip architecture (SoC) with integrated memory and graphics controller</p> <p>FCBGA1744 package - directly soldered onto the mainboard</p> <p>Processor cores: total 10</p> <ul style="list-style-type: none"> - Performance Cores: 2 P-Cores (4 Threads) at 1.3 / 4.4 GHz basis/turbo clock - Efficient Cores: 8 E-Cores at 0.9 / 3.3 GHz basis/turbo clock <p>Smart Cache: 12 MB</p> <p>TDP wattage: 15 W maximum</p> <p>Manufacturing process: Intel 7 (10 nm)</p> <p>Maximum Tjunction Temperature: 100 °C</p>
INTEGRATED GRAPHICS	<p>Intel® Iris® Xe Graphics with 80 Execution Units (EU)</p> <p>Graphics Max Dynamic Frequency: 1.20 GHz</p> <p>Supports up to three independent screens:</p> <ol style="list-style-type: none"> 1) Built-in Full-HD display (supports 1080p/60) 2) HDMI 2.0b port (supports 1080p/60 and 2160p/60) 3) VGA port (supports 1080p/60)
UEFI BIOS	<p>Supports resume after power failure</p> <p>Supports Wake on LAN (WOL)</p> <p>Supports Power on by RTC Alarm</p> <p>Supports boot from M.2 SSD cards and USB devices</p> <p>AMI BIOS in 32 MB EEPROM with SPI interface</p> <p>Supports hardware monitoring and Watchdog function</p> <p>Supports Unified Extensible Firmware Interface (UEFI)</p>
TPM MODULE	<p>Hardware Trusted Platform Module (Infineon SLB9670VQ2 TPM 2.0)</p>

POWER ADAPTER	<p>External 90 W power adapter (fanless) Model FSP090-RBBM1 Medical Safety IEC 60601-1, Meet EN55011 and FCC Class B Input: 90~264 V AC, 50/60 Hz Output: 19 V DC, 4.74 A, max. 90 W DC Connector: 5.5/2.5 mm (outer/inner diameter) AC mains cable: 3 pins, with C5/C6 coupler (called "Mickey Mouse" or "Clover-leaf") for the power adapter and CEE-7/7 plug with earth-contact (type E+F) for the power outlet DOE Energy Efficiency Level VI No Load Power Consumption = 0.21W Dimensions: 140 x 71 x 22 mm</p>
DC INPUT CONNECTOR	<p>DC Input Connector: 5.5 / 2.5 mm (outer/inner diameter). The DC-input of the computer supports 19V±5%. Optional extended voltage range of 9 to 36V with the Shuttle Accessory VOL01.</p>
MEMORY SUPPORT	<p>2x SO-DIMM slot with 262 pins Supports DDR5-4800 (PC5-38400) SDRAM at 1.1 V Supports Dual Channel mode Supports a maximum of 32 GB per DIMM, maximum total size: 64 GB</p>
M.2 SLOT FOR SSDs	<p>The M.2 2280 M slot provides the following interfaces: - PCI-Express Gen. 4.0 X4 - SATA v3.0 (max. 6 Gbps) It supports M.2 SSD cards with a width of 22 mm and a length of 80 or 42 mm (type 2280 or 2242). Supports M.2 SATA SSDs (with B+M key) and M.2 PCIe NVMe SSDs (with M key) with auto interface detect</p>
WEBCAM	<p>Integrated Full-HD 2.0 Megapixel (1920 x 1080) camera</p>
AUDIO AND SPEAKERS	<p>Audio Realtek® ALC888S High-Definition Audio Two analog audio connectors (3.5 mm) on the back panel: 1) 2 channel line out (headphones) 2) microphone input Digital multi-channel audio output: via HDMI Two Two built-in speakers (2x 2W Stereo)</p>
DUAL INTEL 2.5G LAN	<p>Dual network with RJ45 ports and Intel i226 network chips (black connector: Intel i226V, yellow connector: Intel i226LM) Supports 10 / 100 / 1000 / 2500 MBit/s operation Supports WAKE ON LAN (WOL) Supports network boot by Preboot eXecution Environment (PXE)</p>
WIRELESS NETWORK (WLAN)	<p>Built-in M.2-2230-E WLAN card with two internal antennas WLAN Controller Realtek RTL8821CE Supports WiFi IEEE 802.11b/g/n/ac in the 2.4 / 5 GHz band, 1T1R Supports 20 / 40 / 80 MHz channel bandwidth Security: supports WPA(-PSK), WPA2(-PSK), WEP 64/128 bit, IEEE 802.11x, IEEE 802.11i Supports Bluetooth 4.2 in the 2.4 GHz band</p>
BACK PANEL CONNECTORS	<p>Power Button (another button available in an easily accessible place) HDMI 2.0b (digital video+audio) D-Sub/VGA (analog video) 4x USB 3.2 Gen 1 Type A (max. 5 Gbps) 4x USB 2.0 2x Intel 2.5G LAN (RJ45, i226V and i226LM) 1x Serial Port (DB-9/D-sub, RS232) Microphone input (3.5 mm) Audio Line-out / Headphones (3.5 mm) DC-input connector for external power adapter Potential equalization pin (POAG) according to DIN 42801 including cable</p>
ENVIRONMENTAL SPECIFICATIONS	<p>Operating temperature: 0 ~ 40 °C Storage temperature: -20 ~ 60 °C Permitted relative humidity: 20 ~ 80 % (non-condensing)</p>

CONFORMITY AND CERTIFICATIONS

EMC: CE EN60601-1-2:2015+A1:2021, EN IEC61000-3-2:2019+A1:2021, FCC Part 18, FCC/OST MP-5

Safety: cTUVus(ANSI/AAMI ES60601-1:2005/A2:2021), CB(IEC 60601-1:2005/AMD2:2020)


RF: EU, US, Taiwan

This device is classed as a technical information equipment (ITE) in Class A. Class A is for products used in commercial and industrial areas. The CE-mark approves the conformity by the EU directives:

- (1) 2014/30/EU relating to electromagnetic compatibility (EMC),
- (2) 2014/35/EU relating to Electrical Equipment designed for use within certain voltage limits (LVD),
- (3) 2009/125/EC relating to eco design requirements for energy-related products (ErP)
- (4) 2014/53/EU Radio Equipment Directive (RED)

SHUTTLE Panel PC M15AL01-i5 — TECHNICAL DRAWING

Overall dimensions: 394.3 x 256.2 x 48.9 mm (WHD)



VESA mount and stand are not included in the scope of delivery.