

19.5" All-in-One PC for POS, POI, Kiosk, Office Applications

The Shuttle XPC all-in-one P90U is the largest member in Shuttle's product range and is powered by an Intel Ultra-Low-Voltage (ULV) processor, which helps improve on power consumption and computing power. Thanks to its passive cooling, the system is virtually noiseless, maintenance-free and approved for 24/7 nonstop operation. Particularly suitable for vertical applications is the arrangement of connectors at the bottom and the IP54 compliant front panel which is dust-protected and protected from splashing of water.

XPC all-in-one Barebone P90U



Feature Highlights

All-in-One Design	<ul style="list-style-type: none"> XPC all-in-one with touchscreen Dimensions: 487 x 321 x 44 mm 100 mm VESA mount capable IP54 compliant front panel Approved for 24/7 nonstop operation
Display & Graphics	<ul style="list-style-type: none"> 49.5 cm (19.5") LCD Display Resolution: 1600 x 900 pixel Capacitive 10-point multi-touchscreen Integrated Intel HD 610 graphics HDMI 1.4 + D-Sub/VGA Video output
CPU & Cooling	<ul style="list-style-type: none"> Intel Celeron 3865U, 1.8 GHz, 15 W TDP Fanless heatpipe cooling system
Storage (not included)	<ul style="list-style-type: none"> Supports max. 2x 16 GB DDR4-2133 SO-DIMM Supports one 2.5" SATA hard disk / SSD Supports one M.2-2280 SSD (SATA / PCIe) Supports internal USB stick (USB 2.0, type A)
Operating System	<ul style="list-style-type: none"> Operating system is not included Supports Windows 10 (64-bit) & Linux (64-bit)
Connectivity	<ul style="list-style-type: none"> HDMI 1.4, D-Sub/VGA 2x USB 3.0, 4x USB 2.0, internal port: 1x USB 2.0 Microphone input, headphones output Gigabit LAN, Wireless LAN 802.11ac, BT 4.1
Optional	<ul style="list-style-type: none"> PCL71: 2x COM, 1x LPT POS01: 4x COM (2x D-Sub, 2x RJ45), LPT, RJ11 PNFC01: NFC support Supports LTE/USB stick + two external antennas
Built-in	<ul style="list-style-type: none"> SD card reader 2.0 Megapixel HD webcam 2x 2 W speakers Electret Condenser Microphone
Power Supply	<ul style="list-style-type: none"> External fanless power adapter, 65 W / 19 V DC-in supports 12 V and 19 V voltage
Warranty	<ul style="list-style-type: none"> 24 months Bring-in Service

Images for illustration purposes only.



19.5" Touchscreen



Nonstop operating



Fanless cooling



Front protected: dust & water



Up to four COM ports



Supports Windows 10 & Linux (64-bit)



Wireless and Wired Network



2x USB 3.0
4x USB 2.0



Watchdog Hardware

Shuttle XPC all-in-one P90U – Overview



- | | | | | | |
|---|-------------------------------------|----|----------------------------|----|-----------------------------|
| 1 | Power LED, HDD LED | 9 | Kensington lock | 17 | Audio Line-out (headphones) |
| 2 | Webcam | 10 | Optional LTE antennas | 18 | Microphone Input |
| 3 | Microphone | 11 | D-Sub/VGA Video Output | 19 | 100 x 100 mm VESA mount |
| 4 | Touchscreen LCD display | 12 | DC-input for Power Adapter | 20 | Stand |
| 5 | Stereo speakers | 13 | 2x USB 2.0 | 21 | Power Button |
| 6 | Optional NFC | 14 | RJ45 Gigabit LAN | 22 | SD Card Reader |
| 7 | Optional: 2x COM + LTP (PCL71) | 15 | 2x USB 3.0 | 23 | 2x USB 2.0 |
| 8 | Optional: 4x COM, LPT, RJ11 (POS01) | 16 | HDMI Video Output | | |

© 2018 by Shuttle Computer Handels GmbH (Germany). All information subject to change without notice. Pictures for illustration purposes only.