
XPC User Guide

**For the : XPC MAX
SB83G5C**

Shuttle Mainboard EMI Test Statement

Shuttle mainboards have been through EMI tests according to the following series of regulations: EN55022/CISPR22/AS/NZS3548 Class B, EN55024 (1998/AS/NZS), EN4252.1 (1994), EN61000, ANSI C63.4 (1992), CFR47 Part 15 Subpart B, and CNS13438 (1997). The items tested are illustrated as follows:

(A) Voltage: AC 110V/60HZ & AC 230V/50HZ

(B) Tested Product Information:

Product Name: PC Mainboard

Status: Sample

Model Name: SB83G5C

S/N: N/A

CPU:

External Frequency: 133 MHz

Intel Pentium 4, LGA 775 Processor: 2.40/ 2.53/ 2.66/ 2.80 GHz

External Frequency: 200 MHz

Intel Pentium 4, LGA 775 Processor: 2.8/ 3/ 3.2/ 3.4/ 3.6 GHz

Serial Port: one port with 9 pins

VGA Port: one port with 15 pins

Keyboard Port: one port with 6 pins

Mouse Port: one port with 6 pins

USB 2.0 Port: four ports with 4 pins respectively

1394 Port: one port with 4 pins and one port with 6 pins respectively

LAN Port: one port with 8 pins (10Mbps/100Mbps/1000Mbps)

Center/Bass-Out Port: four ports

Mic-In Ports: one port

Line-In Ports: one port

SPDIF-Out (Coaxial) Port: one port

SPDIF-Out (Optical) Port: one port

SPDIF-In (Optical) Port: one port

Clear CMOS button: one port

DIMM Memory (optional): DDR 400 256 MB *2

Power Cable: Detachable and Shielded (with a GND pin)

Monitor: CRT+DVI

Maximum Resolution: 1280 X 1024 V:60Hz

All CPUs have completely been tested, and values offered by the worst EMI combination of CPU external frequency are listed as follows:

Test Mode	External Frequency	CPU	CPU Open/Close
1	200MHz	P4 3.6 GHz	Close
2	200MHz	P4 3.6 GHz	Open
3	133MHz	P4 2.8 GHz	Close
4	133MHz	P4 2.8 GHz	Open

(C) Remedy for the Tested Product & Its EMI Interference:

Remedy: N/A

EMI Interference:

Crystal : 14.318MHz(X2)/ 25MHz(X3)/ 32.768KHz(X1)/ 24.576MHz(X4)

Clock Generator: U5

(D) Supported Host Peripherals:

Component	Brand	Model No. / Spec.
HDD	Seagate	S5026FB83
FDD	Panasonic	SU-256A888PC, 1.44MB
CD-ROM	BenQ	652A-6N2, 52X
Memory x2	Kingston	KVR400X64C25/256, 256MB
NTXC Tuner Card	Shuttle	PM 11
PAL Tuner Card	Shuttle	PM 12
Power	Shuttle	PC40N250EV, 250W

(E) Notices for Assembling Computers:

1. An I/O shielding should be contacted with I/O metallic parts of a mainboard.
2. Cables should appropriately be arranged and fixed in a case. Follow instructions:
 - Leave IDE cables not crossed upon CPU and SDRAM;
 - Leave power cables minimum in length, and not crossed upon a mainboard;
 - Leave CPU fan cables minimum in length, and not near CPU;
 - Leave cables on panels and other spare cables tied in a computer case.
3. Make sure an EMI shielding attached to a case has been properly installed.
4. Make sure a 5.25" drive and screws are fastened to the case (EMI shielding).
5. Make sure the case is in contact with EMI connection points.
6. Make sure there is no cleft in the case.
7. Make sure a PCI door is bound to a case.
8. Make sure cables of other devices (fans or some others) are fixed in a case.

Shuttle®

XPC Installation Guide

Copyright

Copyright® 2005 by Shuttle® Inc. All Rights Reserved.

No part of this publication may be reproduced, transcribed, stored in a retrieval system, translated into any language, or transmitted in any form or by any means, electronic, mechanical, magnetic, optical, chemical, photocopying, manual, or otherwise, without prior written permission from Shuttle® Inc.

Disclaimer

Shuttle® Inc. shall not be liable for any incidental or consequential damages resulting from the performance or use of this product.

This company makes no representations or warranties regarding the contents of this manual. Information in this manual has been carefully checked for reliability; however, no guarantee is given as to the correctness of the contents. In the interest of continued product improvement, this company reserves the right to revise the manual or include changes in the specifications of the product described within it at any time without notice and without obligation to notify any person of such revision or changes. The information contained in this manual is provided for general use by customers.

This device complies with Part 15 of the FCC Rules, Operation is subject to the following two conditions:

1. This device may not cause harmful interference.
2. This device must accept any interference received, including interference that may cause undesired operation.

Trademarks

Shuttle is a registered trademark of Shuttle Inc.

Intel and Pentium are registered trademarks of Intel Corporation.

PS/2 is a registered trademark of IBM Corporation.

AWARD is a registered trademark of Award Software Inc.

Microsoft and Windows are registered trademarks of Microsoft Corporation.

General Notice

Other brand and product names used herein are for identification purposes only and may be trademarks of their respective owners.

Safety Information


Read the following precautions before setting up a Shuttle XPC.

CAUTION

Incorrectly replacing the battery may damage this computer. Replace only with the same or equivalent as recommended by Shuttle. Dispose of used batteries according to the manufacturer's instructions.

Installation Notices


Do not place this device underneath heavy loads or in an unstable position.



Do not expose this device to high levels of direct sunlight, high-humidity or wet conditions.



Do not use or expose this device around magnetic fields as magnetic interference may affect the performance of the device.



Do not block the air vents to this device or impede the airflow in any way.




TABLE OF CONTENTS

1 Function Introduction	1
1.1 XPC Introduction	1
1.2 Model Specifications	2
1.3 XPC Exterior Dissection	3
1.3.1 XPC Front	3
1.3.2 XPC Back	4
1.4 Hardware Installation	5
1.4.1 FB83 mainboard illustration	5
1.4.2 Jumper Settings	6
Front Panel Connector (JP9)	6
Fan Connectors (FAN1/FAN2/FAN3)	7
CD-IN (J1)(Black)/LINE-IN (J4)(Blue) Connectors	7
Wireless Keyboard and Mouse Connectors (JP7)	7
IR Connector (JP8)	8
Parallel Port Header-EXT. Print Port (JP5)	8
Extended USB Connectors (USB2/USB3/USB4)	9
SPDIF-Out Connector (J2)(White)	9
1.5 Remote Control Key Definition	10
1.6 Shuttle Versatile Front-panel Display (VFD) Introduction	11
2 XPC Installation Guide	12
2.1 Installation	12
2.1.1 Remove the Cover	12
2.1.2 Remove the Rack	13
2.2 CPU and ICE Installation	14
2.2.1 Remove the ICE Module	14
2.2.2 Install the CPU	16
2.2.3 Install the ICE Module	18
2.3 DDR Installation	19

2.4 Cable and Rack Installation	21
2.4.1 Install the FDD Cable	21
2.4.2 Install the IDE HDD Cable	22
2.4.3 Install a Serial ATA HDD Cable	23
2.4.4 Install the Rack	24
2.5 Peripheral Installation	26
2.5.1 Install the IDE HDD	26
2.5.2 Install the Serial ATA HDD	27
2.5.3 Install the Floppy Drive	27
2.5.4 Install an Optical Drive	27
2.6 Accessories Installation	31
2.6.1 Install PCI Express Card	31
2.7 Final Touches	33
2.7.1 Close the Chassis Cover	33
2.7.2 Install Front Feet	33
2.7.3 Complete	34
2.8 XPC Accessories	34
2.9 Tech Support	34
2.A Technical Notes: Clear CMOS Button	35
2.B TV tuner setup notes	35
FM signal antenna	35
TV signal cable	36
Multi-function Audio/Video port	36
3 Driver and Software Installation	37
3.1 Mainboard CD Overview	37
3.1.1 Install Mainboard Software	38
3.2 Install XPC Tools Software	39
3.3 Install XPC MAX Software	40

4 Software Utility	41
4.1 XPC Configuration	41
Media Library Configuration	41
DVD Configuration	41
4.2 XPC MAX Interface	41
Ten-foot Interface	41
4.3 Setting Up XPC MAX	42
General Settings	42
TV Settings	42
Picture Settings	43
DVD Settings	43
4.4 Using XPC MAX	44
TV Mode	44
Watching TV	44
Play DVD/VCD	46
Pictures Mode	48
Slide Show	49
Play Video Clips	50
Music Mode	51
Listening to Music	52
Playlist	53
Listening to Radio	54
Appendix	56
Enter the BIOS	56
THE MAIN MENU	57
STANDARD CMOS FEATURES	59
ADVANCED BIOS FEATURES	62
ADVANCED CHIPSET FEATURES	67

INTEGRATED PERIPHERALS	69
POWER MANAGEMENT SETUP	74
PNP/PCI CONFIGURATIONS	78
PC HEALTH STATUS	80
Frequency/Voltage Control	82
LOAD FAIL-SAFE DEFAULTS	84
LOAD OPTIMIZED DEFAULTS	84
SET PASSWORD	85
SAVE & EXIT SETUP	86
EXIT WITHOUT SAVING	86

1 Function Introduction

■ 1.1 XPC Introduction

The Shuttle XPC is the original high-performance Small Form Factor (SFF) computer. Since the first model was introduced in 2001, the XPC has become the world's best-selling SFF computer brand.

Each Shuttle XPC is sold as a "barebone" computer ~ chassis, power supply and motherboard. The user must add his own processor, memory, drives and, as applicable, expansion cards. The XPC has been designed to be easily assembled and configured directly by the end user. Consumers can choose to buy preconfigured, ready-to-run XPC's as well ~ a list of Shuttle-authorized value-added resellers can be found at www.shuttle.com.

The Shuttle XPC owes its popularity to its unique combination of small-size, high-performance and near universal component compatibility. However, unlike ordinary desktop computers, Shuttle XPC's have been engineered as complete systems.

The XPC concept can be summarized as:

Use of high-performance, industry-standard components; Minimum size possible, while preserving component compatibility and system expansion; Focus on quality ~ a commitment to quality construction, materials and industrial design.

To meet the above requirements, Shuttle has created and patented dozens of new technologies, including the Integrated Cooling Engine (ICE), which extend and enhance the personal computing experience while reducing heat, noise and space requirements.

Thank you for choosing the Shuttle XPC!



■ 1.2 Model Specifications

Form Factor

Shuttle Small Form Factor

Processor

533/800MHz FSB Intel Pentium 4 (LGA775)

Chipset

Intel 915G + ICH6-R

Memory

(2) 184 pin 333/400 Dual Channel DDR DIMMs

4GB capacity, Max.2GB per DIMM

Audio

Realtek ALC658 5.1 channel audio

Ethernet

Marvell 88E8001 (1) PCI slot

10/100/1000 Mb/s LAN operation (1) PS2 Keyboard/Mouse

IEEE 1394a

VIA VT6307, 1394 OHCI v1.0 compliant, Up to 400Mb/s data transfer rate

Serial ATA

ICH6-R integrated SATA, Dual Channel UDMA 150MB/s S-ATA,
Support RAID 0,1, JBOD

Onboard headers & connectors

(1) ATA100 IDE connector

(1) Floppy connector

(3) Fan connectors

(1) CD_in header

(1) Power & reset header

(2) SATA connectors

(1) IR header

(1) Line_in header

(2) 1x5 pin USB 2.0 headers

(1) 2x5 USB 2.0 header

(1) GPIO header

(1) Printer port header

(1) Power connector (reserved for VGA card)

PSU

Output:250 Watt, Input: 110/230V AC, Active PFC, FCC/CE/UL/TUV/CB certificated

Chassis


G5, Dimension:200(W)x185(H)x280(L), (2) 3.5" bays, (1) 5.25" bay

■ 1.3 XPC Exterior Dissection

Note : Shuttle offers a variety of different XPC models loaded with various options. The illustration below will help familiarize you with the included features in your new XPC.

■ 1.3.1 XPC Front

1. Eject button
2. 5.25" Bay
3. 3.5" Bay
4.  Reset
5.  HDD LED
6.  Power LED
7.  Power switch



8. Versatile Front-panel Display (VFD)

9.   Mic
10.   Headphones
11.   USB ports
12.   FireWire® 400 mini port

1.3.2 XPC Back

1. **OUT**  SPDIF-out (Optical)

2. AC power socket

3.   COM port

4.   VGA port

5.   SPDIF-in port

6.   FireWire® 400 port

7.   PS/2 Mouse

9.   LAN port

11.   SPDIF OUT (Coaxial)

13.   Central/Bass

15.   Front-out (R/L)

17. FM in Port

19. Multi-function Video/Audio Port

(a) Audio-in Port


(b) Audio-out Port

(c) Composite video in Port

(d) S-video in Port

A. Wireless LAN perforation

B. Parallel port perforation



8.   PS/2 Keyboard

10.   USB ports

12.   Line-in port


14.   Rear-out (R/L)

16.  Clear CMOS button

18. TV RF in Port


■ 1.4 XPC Mainboard

■ 1.4.1 FB83 mainboard illustration



■ 1.4.2 Jumper Settings

Several hardware adjustments are made by setting jumpers on the mainboard. To successfully change jumper settings, you will need to locate pin#1. In this manual, pin#1 is represented by a white square, other pins are represented by a circles. An illustration is shown below for your reference:




Jumpers with two pins are shown as  for Closed [On] or  for Open [Off]. To Short jumper pins, simply place a plastic jumper cap over the desired pair of pins.

Caution!

1. Do not remove the mainboard from its case.
2. Do not touch the components on the mainboard. When installing components, pay special attention not to man handle sensitive components on the mainboard.
3. Wear an antistatic wrist strap or take other suitable measures to prevent electrostatic discharge (ESD) whenever handling this equipment or installing components.

Front Panel Connector (JP9)

Header JP9 can be used to provide operation status signals to the front daughterboard. Note that this is an alternative header to the 50pin streamline header that also connects the motherboard to the front daughterboard.




Pin Assignments (JP9):

1 = HDLED_PU	2 = GLEDA
3 = HDLED	4 = GLEDB
5 = Reset_SW	6 = Power_SW
7 = GND	8 = GND
9 = NC	10 = KEY

Fan Connectors (FAN1/FAN2/FAN3)


This mainboard features three onboard 12V cooling fan connectors. These fans are referred to as; System (FAN1), Chipset (FAN2) or Auxillary (FAN3) cooling fans. Refer to the illustration below for more information about the fan connectors located on this mainboard.



Note : Both cable wiring and type of plug may vary depending on the fan maker. Keep in mind that the red wire must always be connected to the + 12V header and the black wire to the ground (GND) header.

CD-IN (J1)(Black)/ LINE-IN (J4)(Blue) Connectors

Port J1(Black) and J4(Blue) are used to connect stereo audio inputs from a CD-ROM, TV-tuner or MPEG card.




Pin Assignments (J1/ J4):

- 1 = CD-in Left / Line-in Left
- 2 = CD-GND / Line-GND
- 3 = CD-GND / Line-GND
- 4 = CD-in Right / Line-in Right

Wireless Keyboard and Mouse Connectors (JP7)

JP7 header provides support for a wireless keyboard and mouse. The four mini Jumpers must be set on the 5-6, 7-8, 9-10 pins and 11-12 pins when this header is not in use.




Pin Assignments (JP7):

- | | |
|-------------|------------|
| 1 = VCC | 2 = VCC |
| 3 = Ground | 4 = KEY |
| 5 = MSCLK | 6 = MS_CK |
| 7 = MSDATA | 8 = MS_DK |
| 9 = KBCLK | 10 = KB_CK |
| 11 = KBDATA | 12 = KB_DK |

IR Connector (JP8)

JP8 supports IrDA transfer devices. To enable IrDA transfer devices, install appropriate IR connectors according to the instructions belows:



Pins Assignment:

- 1 = NC
- 2 = KEY
- 3 = VCC
- 4 = Ground
- 5 = IrTx
- 6 = IrRx


Note : Before connecting your IR device, ensure the IR onboard pin allocation matches the IR device. Incorrect installation may damage your IR device.

Step1 : Attach the 6-pin infrared device cable to JP8.
(Refer to the above diagram for IR pin assignment.)

Step2 : This mainboard supports IrDA and Normal transfer modes.

Parallel Port Header-EXT. Printer Port (JP5)

A DB25 male parallel port header is located near the rear panel of the mainboard. The header is used to connect a parallel port socket (PC8) to the mainboard. The parallel printer port can be purchased from Shuttle as an optional accessory.



Pin Assignments (JP5):

- | | | |
|--------------|--------------|-------------|
| 1 = P_-STB | 2 = P_-PPD0 | 3 = P_-PPD1 |
| 4 = P_-PPD2 | 5 = P_-PPD3 | 6 = P_-PPD4 |
| 7 = P_-PPD5 | 8 = P_-PPD6 | 9 = P_-PPD7 |
| 10 = P_-ACK | 11 = P_-BUSY | 12 = P_-PE |
| 13 = P_-SLCT | 14 = P_-AFD | 15 = P_-ERR |
| 16 = P_-INIT | 17 = P_-SLIN | 18 = GND |
| 19 = GND | 20 = GND | 21 = GND |
| 22 = GND | 23 = GND | 24 = GND |
| 25 = GND | 26 = KEY | |


 **Extended USB Connectors (USB2/USB3/USB4)**

These headers are used to connect auxiliary USB devices to the mainboard. These headers are directional and will only allow USB cables to be connected in one direction.

Pin Assignments (USB2):

- 1 = GND
- 2 = GND
- 3 = Data5 +
- 4 = Data5-
- 5 = VCC


USB2



Pin Assignments (USB4):

- 1 = VCC
- 2 = VCC
- 3 = Data2-
- 4 = Data3-
- 5 = Data2 +
- 6 = Data3 +
- 7 = Ground
- 8 = Ground
- 9 = Key
- 10 = N/C


USB4



Pin Assignments (USB3):


- 1 = GND
- 2 = GND
- 3 = Data4 +
- 4 = Data4-
- 5 = VCC

USB3



 **SPDIF-out Connector (J2) (White)**


Port J2 provides the mainboard connection for the SPDIF-out signal port.



Pin Assignments (J2):

- 1 = SPDIF-out
- 2 = VCC
- 3 = GND

■ 1.5 Remote Control Key Definition



■ 1.6 Shuttle Versatile Front-panel Display (VFD) Introduction

The VFD panel included in this XPC is designed to serve as an alternative display for enhanced multimedia enjoyment. As such, the VPD panel can display; music track info, time, track time, DVD info, DVD play length, TV channel, radio stations, picture information and much more. Better still, this VFD panel delivers all this content without obstructing your main display or vision.



 **Text Display**

 **Time**

 **Radio**

 **Music**

 **DVD/VCD**

 **TV**

 **Picture**

 **Rew (Rewind)**

 **Record**

 **Play**

 **Pause**

 **Stop**

 **FF (Fast Forward)**

 **Repeat**

 **Shuffle**

 **Mute**

 **Volume**


2 XPC Installation Guide

■ 2.1 Installation


Note : For safety reasons, please ensure that the power cord is disconnected before opening the case.

■ 2.1.1 Remove the Cover

1. Unscrew the three thumbscrews.




2. Slide the cover backwards and upwards.




■ 2.1.2 Remove the Rack

1. Unfasten the rack mount screws.



2. Remove the rack.



Rack




■ 2.2 CPU and ICE Installation

■ 2.2.1 Remove the ICE Module


1. Unfasten the ICE fan thumbscrews on the back of the chassis.




2. Unplug the fan power connector.




3. Unfasten the four attachment screws.



4. Remove the ICE module from the chassis and put it aside.



ICE Heat-Pipe Module




■ 2.2.2 Install the CPU

Note : This 775 pin socket is fragile and easily damaged. Always use extreme care when installing a CPU and limit the number of times that you remove or change the CPU.



1. Remove the protective cover.



2. First unlock and raise the socket lever, then open the load plate (be careful not to touch the socket pins during this process).




3. Orientate the CPU and socket, aligning the yellow triangle on the corner of the CPU with the triangle on the socket. Making sure the CPU is perfectly horizontal, insert the CPU into the socket. Close the load plate, lower the CPU socket lever and lock in place.




4. Spread an even layer of thermal compound on the CPU die.

Thermal compound application area





■ 2.2.3 Install the ICE Module


1. Place the ICE the module on top of the CPU and align the spring loaded screws with the mainboard mounting holes.




2. Screw the ICE module to the mainboard. Note to press down on the opposite diagonal corner while tightening each screw.



3. Attach the fan power connector to the extension cable connected to the mainboard.



4. Fasten the Smart Fan to the chassis with the four thumbscrews.



■ 2.3 DDR Installation

Memory Compatibility : Install memory in any or all of the banks according to the combinations shown below.


TOTAL 2 DIMM in Single or Dual Channel Mode up to 4GB and 2GB per DIMM						
Density	256 Mbit		512 Mbit		1024 Mbit	
Device Width	X8	X16	X8	X16	X8	X16
Single Side	256MB	128MB	512MB	256MB	1024MB	512MB
Double Side	512MB	N/A	1024MB	N/A	2048MB	N/A

- Note:**
1. Maximum installable memory is 4GB.
 2. Double-side X16 DDR-SDRAM chips are not supported.
 3. Registered DIMMs are not supported.
 4. Only unbuffered without ECC DIMM are supported.
 5. Does not support X4 DDR-SDRAM.




Note : No jumper settings are required to configure memory.
The system BIOS utility automatically detects the memory settings.
Check the total installed system memory value in the BIOS menu.

Install a DDR module in DIMM1/DIMM2.


1. Unlock the DIMM latch.



2. Align the DDR module's cutout with the DIMM slot notch. Slide the DDR module into the DIMM slot.



3. Check that the latches are closed, and the DDR module is firmly installed.




■ 2.4 Cable and Rack Installation


■ 2.4.1 Install the FDD Cable

Note : If you do not wish to install a FDD, proceed to step 2.4.2.

1. Plug the FDD cable in the FDD header (FDD1).



2. Fold the FDD cable under the power supply.



3. Fix the FDD cable to the power and chassis rail with the supplied adhesive tape.



Adhesive



Note : Only complete section 2.4.2 if you wish to install a IDE hard drive. If you do not wish to install an IDE hard drive, proceed to section 2.4.3.



■ 2.4.2 Install the IDE HDD Cable

1. Remove the IDE cable.


IDE (Optical drive) cable




2. Take out the triple head IDE cable from accessory box. Connect the end labelled mainboard to the IDE1 header.



Purse lock




3. Loosen the purse lock and separate the IDE HDD/FDD power cable (white).




■ 2.4.3 Install a Serial ATA HDD Cable

Note : Only complete this step if you will install two Serial ATA HDDs.


1. If you want to install a second Serial ATA HDD, take the Serial ATA cable from accessory box and plug it in the ATA2 header.



Serial ATA Cable




- Loosen the purse lock and separate the FDD power cable (white) and Serial ATA HDD power cable (black).




■ 2.4.4 Install the Rack

- Place the HDD in the rack and secure with screws from the side.



Note : Secure with two screws on each side.

- Place the FDD in the rack and tighten with its own screws.




Note : The second screw is located on the opposite side of rack.

**Note : Refer to section 2.4.4-3A if installing an IDE HDD.
Refer to section 2.4.4-3B if installing a Serial ATA HDD.**


- 3A. Place the IDE HDD and power cables in the rack clip located on the underside of the rack mount.

Rack Clip



- 3B. Place the Serial ATA HDD power cables in the rack clip located on the underside of the rack mount.

Rack Clip




4. Place the rack in the chassis.



Note : As you insert the rack, use a small amount of pressure to pull the tuner card away from the rack. Release the tuner card and ensure that the rubber knob sits firmly between the rack and the tuner card to avoid power shorts.

5. Refasten the rack.



■ 2.5 Peripheral Installation

Note : Refer to section 2.5.1 if installing an IDE HDD.
Refer to section 2.5.2 if installing a Serial ATA HDD.

■ 2.5.1 Install the IDE HDD

1. Connect the HDD power and IDE cables to the HDD.

IDE HDD Cable

IDE Power Cable




2. Jumper settings. If you are using an IDE HDD, you will need to set the jumpers on the HDD to master and the optical drive to slave. Refer to your peripherals for details on jumper positioning.

Optical Drive jumper




IDE HDD jumper



Details on jumper positioning


■ 2.5.2 Install the Serial ATA HDD

1. Connect the Serial ATA and power cables to the HDD.




■ 2.5.3 Install the Floppy Drive

1. Connect the FDD and power cables to the Floppy drive.




■ 2.5.4 Install an Optical Drive


1. Loosen the purse lock around the optical drive and power cables than slide the optical drive into the chassis.



- Open the stealth drive door. Check the alignment of the drive's eject button with this XPC's drive eject mechanism. Press the external eject button to check. If it is well aligned, proceed Step 8. If it is poorly aligned, adjust the internal control rod to suite.




Adjust Control rod




Note : After adjusting the position of the control rod you may find that it still does not align well with the eject button. In this case, you will need to change the size of the control rod. Follow the steps below.


- Remove the front panel USB cable.





- Remove the front panel.



Unlock the four chips




5. Remove the 1.2 mm control rod.




6. Take out the 1.8 mm control rod from the accessory box and insert it in the slot as show.



7. Connect the USB cable. Reattach the front panel. Check the alignment and adjust if necessary.




8. Plug the optical drive cable and power cable into the optical drive.



Note : If you are installing an IDE HDD, use the same cable for the HDD and the optical drive.

9. Fasten the four side screws.



■ 2.6 Accessories Installation

■ 2.6.1 Install PCI Express Card

1. A PCI Express VGA card will be used to demonstrate this installation procedure.




PCI Express card



2. Unfasten the expansion slot bracket screws.

PCI Express slot


3. Remove the back panel bracket and put the bracket aside.



Lift up

Slot Bracket

4. Install the PCI Express VGA card into the PCI Express slot.




5. Secure the bracket.



■ 2.7 Final Touches

■ 2.7.1 Close the Chassis Cover

1. Replace the cover and refasten the thumbscrews.



■ 2.7.2 Install Front Feet

1. Take out the two front feet from the accessory box.



Front feet

2. Screw the front feet to the base of the chassis.



■ 2.7.3 Complete



■ 2.8 XPC Accessories

Shuttle offers over 25 great upgrade and modding kits for your XPC. Visit our website at <http://www.shuttle.com> for more information or speak to your local retailer.


■ 2.9 Tech Support

1. Shuttle Inc.
<http://www.shuttle.com>
2. Tech Support
<http://global.shuttle.com/Support/Support.asp>
3. Download
<http://global.shuttle.com/Download/Download.asp>
4. Barebone FAQ
http://global.shuttle.com/Support/SupportFAQ_Brb.asp
5. Barebone Support List
http://global.shuttle.com/Support/SupportList_Brb.asp

■ 2.A Technical Notes: Clear CMOS Button

This XPC comes enhanced with an easy-to-use Clear CMOS Button. This button allows users to reset BIOS information to factory default settings.

1. Power down the XPC and remove the power cord.
2. Press the Clear CMOS Button by inserting a pointed object (e.g. a pen nib) into the clear CMOS hole. Keep it pressed for 5 seconds.
3. Reconnect the power cord and turn on the computer.



Clear CMOS button

Note : Remove the power cord before clearing CMOS.

■ 2.B TV tuner setup notes

☞ FM signal antenna:


Take out the radio antenna from the accessory box and attach it to the FM-in jack.



Note : Place the antenna in an elevated location for better reception.

☞ **TV signal cable:**

Connect the TV (antenna/cable TV) cable to the protruding TV RF-in jack.




Note : XPC MAX TV features will only operate if your TV signal cable (antenna or cable TV) is connected.

☞ **Multi-function Audio/Video port :**

Note : This cable connects the XPC to a video cassette recorder (VCR).

1. Take out the MF Audio/Video cable from the accessory box.
2. Connect the MF Audio/Video cable to the AUX jack.
3. Connect the SV/Composite Video input cable to the S-Video/Composite Video jack on your VCR or alternative device.
4. Connect the Audio-out/in cable to the audio input/output jack on your VCR or alternative device.



3 Driver and Software Installation


■ 3.1 Mainboard Driver CD

Note : The CD contents attached in FB83 mainboard are subject to change without notice.

The Mainboard Driver CD contains all the motherboard driver necessary to optimize the performance of this XPC in a Windows(R) OS. Install these drivers after installing Microsoft(R) Windows(R).

Navigation Bar Description :

- ☞ **Install Mainboard Software** - Install Intel Chipset, Intel VGA, Intel IAA, Marvell Giga Lan, Realtek Audio, PM11/PM12 TV, Intel USB 2.0 drivers and DirectX9 Utility.
- ☞ **Install Utility** - Install Acrobat Reader, WinFlash Utility, XPC Tools.
- ☞ **Manual** - XPC MAX SB83G5C user's guide in PDF format.
- ☞ **Link to Shuttle Homepage** - Link to shuttle website homepage.
- ☞ **Browse this CD** - Allows you to see contents of this CD.
- ☞ **Quit** - Close this CD.



■ 3.1.1 Install Mainboard Software

Insert the attached CD into your CD-ROM drive. The CD AutoRun screen should appear. If the AutoRun screen does not appear, double click on Autorun icon in **My Computer** to bring up **Shuttle Mainboard Software Setup** screen.


Click the “**Install Main-board Software**” bar. Individually install the following drivers.

- ☛ Install Intel Chipset Driver
- ☛ Install Intel VGA Driver
- ☛ Install Intel IAA Driver
- ☛ Install Marvell Giga LAN Driver
- ☛ Install Realtek Audio Driver
- ☛ Install PM11/PM12 TV Driver
- ☛ Install Intel USB 2.0 Driver
- ☛ Install DirectX9 Utility



■ 3.2 XPC Tools Software

Created especially for the XPC, XPC Tools includes many useful features to allow you to manage and control your system from the comfort of your Windows operating environment.



Included in this version of XPC Tools are features to allow you to:

1. Manage Performance settings
2. Control Acoustic environment
3. Control Thermals (CPU and System)
4. Monitor System Information
5. Manage Versatile Front-panel Display (VFD) settings
6. Select Hot Keys for your Optical Drive
7. Optimize System settings for certain applications
8. Schedule auto shutdown

To install XPC Tools:

1. Select the utilities bar in the mainboard driver CD.
2. Click on XPC Tools. Follow the on screen instructions.
3. An XPC Tools icon will automatically appear on the desktop following installation. Click this to run XPC Tools.
4. For instructions on how to use XPC Tools, click the help icon on the XPC Tools Menu.

■ 3.3 Install XPC MAX Software

To install XPC MAX, insert the XPC drivers CD into your CD-ROM drive and the CD AutoRun screen should appear. If the Auto Run screen does not appear, double click or run D:\Autorun.exe (assuming that your CD-ROM drive is drive D:).

1. Select XPC MAX from the "install utility" section. This will install XPC MAX on your computer. It is recommended that you close all other applications before continuing. Click **<Next>** to continue, or **<Cancel>** to exit Setup.
2. Please read the following license agreement carefully. You must accept the terms of this agreement before continuing with the installation. Click the **<Next>** button to proceed the installation.
3. Select the folder where you would like XPC MAX to be installed, then click **<Next>**.
4. Please select a program folder. Setup will add program icons to the Program Folder listed below. You may type a new folder name, or select one from the existing folder list. Click **<Next>** to continue.
5. Select the file types for which you want XPC MAX Player to be the default player, then click **<Next>**.

Note : If you have a DVD-ROM drive, you can use it to play video.

6. When the installation is completed, click **<Finish>** to exit Setup.

4 Software Utility

■ 4.1 XPC MAX Configuration

Media Library Configuration

XPC MAX lets you set up your own media library. In this configuration, you can have four libraries for different file types: video, music, picture and playlist. Each library contains and lists paths that you add. After you complete adding paths, XPC MAX will access media files from the designated folders automatically, this means no need to add more files after setup.

DVD Configuration

You can configure several basic settings in the DVD configuration section. Configurations will depend on whether the DVD you are playing has multiple audio and subtitle languages.

Note : You must have a DVD drive to play DVDs.

■ 4.2 XPC MAX Interface

The XPC MAX interface consists of two parts: Ten-Foot interface & auto-hide control panel. These two parts combine to provide the utmost easy-of-use.

Launch XPC MAX by clicking **Start** → **Programs** → **XPC MAX** → **XPC MAX**. The ten-foot interface will display as the default interface. Here you can see and navigate the basic features and settings. Click on a bar to enter this feature. The control panel appears in the bottom of the interface. The Control Panel and top tool bar autohide when not in use.

Ten-foot Interface

Working with XPC MAX's ten-foot interface is easy. All you do is select and click the operation you want, then sit back and enjoy. Easy!

Main Menu Page :



■ 4.3 Setting up XPC MAX

General Settings

Hide Date & Time : You can decide whether to hide the date & time shown on the top bar of the interface. To hide date & time, select the Yes Markers checkbox; to show date & time, select the No Markers checkbox.

Music Visualization : Select this function if you wish to view music visualization whenever you are listening to music. Select no to disable this feature.

Run with Windows Start : This option lets you choose to auto run XPC MAX when you boot into windows. Select Yes to enable this feature.

Enable Animation : You can select to have animation enabled or disabled. Click the Yes checkbox to enable animation; click the No checkbox to disable animation. Animation is by default disabled.

Enable Animation : You can select to have animation enabled or disabled. Click the Yes checkbox to enable animation; click the No checkbox to disable animation. Animation is by default disabled.

Control Panel Auto Hide : This feature lets you control the autohide characteristics of the control panel. Select between 1, 2, 3, 5, 10, 15, 30, 60 or 100 seconds. Select Off to disable this feature.

Display Options : Select between Single or Multiple Displays.

TV Settings

Note : XPC MAX only supports analog TV.

TV settings wizard allows you to set up more than just basic configurations.

TV Source : Select the input source you want to view by clicking the Right or Left Arrow. There are two choices: antenna & cable.

Input Source : You can connect external devices to your computer and view them via XPC MAX. You have three choices: composite, TV, and S-Video.

Record Quality : Change the record quality according to your preference. You have three levels of record quality to choose from: Good, Better & Best. Better is the default setting. The higher the recorded quality selected the more space required.

TV Audio : Select your desired audio support; Mono, SAP or Stereo.

Picture Settings

Configuring your Picture settings gives you total control over the way you view your pictures.

Transition Time : Change duration of the transition for a slide show.

Play in Random Order : Choose whether to view your pictures in random order. Select Yes or No checkbox.

Include SubFolders When searching for your pictures, you might have other subfolders that you must browse through for the specific picture you are looking for. Select Yes or No checkbox.

Transition Effect : While playing a slide show, you can add special effects as pictures rotate from one to the next. Select from up to twenty transition effects.

Music for Sildeshow : You can select Yes or No.

Slideshow Music : After you have specified types of background music, music files will load automatically. Select here for subsidiary category.

Music Category : Here you can set background music for your slide show. Select from up to six music types for slide show background music.

DVD Settings

There are two basic configurations you will need to make; Whether the DVD you are playing is multiple language enabled and whether it contains subtitles.

Audio Language : Select preferred audio language for DVD watching if your DVD supports multiple audio language.

Subtitle Language : Select preferred subtitle language for DVD watching if your DVD supports multiple subtitle language.

Auto Resume : If you want to resume watching DVD after stop, you can choose to Start from last position or Start from the beginning.

Source : Select the source drive for the CD/VCD/DVD playing if you have multiple input device.

Audio Output : XPC MAX supports Analog Output or Digital (S/PDIF).

Speaker Configuration : If your sound card supports multiple channels, click the Right Arrow. Click the Left Arrow to choose between Dolby 2 channel, 4 channel or 6 channel.

■ 4.4 Using XPC MAX


✍ *TV Mode*

Watching TV using XPC MAX provides full screen video in an easy to control environment. With XPC MAX, you can schedule your favorite shows and movies for viewing or recording. XPC MAX also supports TV time shifting, meaning you can pause Live TV and then continue watching without missing a beat.



◆ *Watching TV*

When you enter TV mode for the first time, you are required to do some basic setup. Please select the basic settings button and then **Rescan Channels** to exit.



- Note :**
1. Selected playback controls are available when viewing a previously recorded program.
 2. TV feature is only available if you have a TV Tuner card installed and your cable or antenna plugged in.
 3. XPC MAX only supports analog signals.

Guide	This EPG lets you search for your favorite shows and quickly and easily schedule programs for viewing or recording. (EPG website varies by region. In US, it is TitanTV)
TeleText	Closed caption is a service providing subtitles if available. TeleText is a service for information like commercial, weather or program schedule if available. For service content, please consult your system provider.
Schedule	Create a schedule about when to auto record a television program.
Channel Surfing	Channel surfing is the quickest way to find the show you want. With a 4x4 grid, it has a thumbnail view of each channel starting from the current channel you are viewing. Click on the thumbnail of the channel you want to view, it will tune to the selected channel.
Recorded TV	Recorded TV will lead you to Video mode page. The shows or movies recorded previously will be saved Shared Videos. After you enter Video mode page, the shows or movies that you recorded will be shown in thumbnail. Double-click on the thumbnail to start watching recorded programs.
Take Snapshot	You can capture snapshot of TV programs or recorded TV shows. When the image you like appears, click Take Snapshot bar to capture a still image.
View Snapshots	Clicking on View Snapshots bar will lead you to Pictuer mode page. All the still images that you have captured will be saved in Shared Pictures folder. To view the snapshots, click View Snapshots bar. Entering Picture mode page, you can view your captured images shown as thumbnail. Double-click on it to view.
Settings	There are four options you can set in TV Settings: TV Source, Input Source, Record Quality and TV Audio. Here, you can also ask XPC MAX to auto scan channels by clicking AutoScan button.

Note : The volume should be muted when channel surfing is cycling through the images in the 4x4 matrix.

(The volume should only be audible when playing TV in one individual 4x4 cell.)

Note : Time Shifting records live TV and saves it temporarily on your hard disc, starting from when you click Pause. The Slide bar on the Player Panel indicates how much video you have recorded.

◆ *Time Shifting*


The Time Shifting feature allows you to pause and then replay the live TV. Time Shifting gives you absolute control over how you watch television. You can take a break watching a live show, and pick up where you left off, or instantly jump back to live view.

To launch Time Shifting :

1. On the Player Panel, click Pause button (or press the Space bar on the keyboard).
2. To replay live TV, click Play button or Pause button (or Space bar) again.
You will be watching live TV from where you just paused.
3. To quit Time Shifting when the show is over, click Stop button on the Player Panel.

Play DVD/VCD

XPC MAX is the ideal portal to play all your DVD and VCDs. Just insert the DVD you want to watch and click play. Sit back and enjoy high-quality DVD and awesome audio performance with surround sound (DVD dependant).




XPC MAX includes several options to enhance your DVD/VCD experience:

Menu	Menu leads you back to the main menu of the DVD that you are watching. You can view menu at anytime while watching DVD.
Audio	If your DVD supports multiple audio language, you can select by simply clicking on Audio bar. Audio language available will display on the screen. Make your choice.
Subtitle	If your DVD supports multiple subtitle language, you can select by simply clicking on Subtitle bar. Subtitle language available will display on the video window. Make your choice.
Karaoke	<p>Insert a Karaoke disc, Karaoke feature will be enabled (or else will be grayed-out) and then you can start singing Karaoke with XPC MAX at home. Click on Karaoke bar, choices will display on video window including None, Left Channel, Right Channel & All Channel. Make your choice.</p> <p>Note: Karaoke feature only supports karaoke enabled VCD, SVCD & Karaoke discs.</p>
Take Snapshot	You can capture snapshot of DVD film. When the image you like appears, click Take Snapshot bar to snapshot an still image of it.
View Snapshots	By default, all the still images that you have captured will be saved in Shared Pictures. To view the images that you have captured, click View Snapshots bar. You will be led into Picture mode, where the Captured Images folder shows as a thumbnail. Double-click on it to view your captured images.
Settings	<p>Settings leads you to DVD Settings page. Here, you can set Audio Language, Subtitle Language, Auto Resume, Source, Audio Output & Speaker Configuration. For details, please refer to DVD Settings (Page43).</p> <p>Note: By default, XPC MAX will enter full-screen mode once you start playing DVD. To return to the View Windows mode, you can either press Esc on your keyboard, or double-click or right-click on the full screen.</p>

Picture Mode

XPC MAX lets you view your pictures, wallpaper, and other graphics stored on your computer, quickly and easily. Your pictures are shown in thumbnails with file name, so you can easily find which graphic you want to select.

By default, when you enter Picture mode, XPC MAX will load in pictures stored in **My Pictures > My Documents**. All pictures will be displayed, including those in the subfolders. However, if you prefer to save images in other folders for better management, use **Media Library (Page41)** for increased convenience.



- Tips :**
1. To view the pictures in subfolder, double-click on the folder thumbnail to view the photos it contains.
 2. To view picture information (resolution, created date, size), move your cursor on the picture you want to examine.
 3. To view single picture in full screen mode, double-click on the picture you want to view.
 4. To view pictures in pre/next page, click Up/Down Arrow.

Play Slideshow	Select the pictures you want to play in slide show, and then click Play Slideshow bar to enjoy your slide show. If no pictures are selected, the slide show will play all images contained in the appointed folder.
Sort By Name	Sort your pictures based on the image file name.
Sort By Date	Sort your pictures based on the date they were created.
Rotate Left	Select a picture by clicking on it, and it will then show in the view window. Click the Rotate Left bar to have the selected picture rotate left both in thumbnail and in view window.
Rotate Right	Repeat the same procedure as you do in Rotate Left. Click Rotate Right bar to have the selected picture rotate right.
Other Media	You can view pictures from multiple source. Click Other Media bar, it will display Shared Picture folder and all removable devices attached to your machine. You can view pictures stored in these other source and play slide show as well.
Print Picture	Select the pictures you want to print, and then click Print Picture.
Settings	To view your pictures in slide show, you must first make certain settings to enrich your slide show viewing. For detailed settings, please see Pictures Settings (Page43).

◆ **Slide Show**

With XPC MAX, you can turn your pictures into an exciting slide show with music and cool transition effects. Furthermore, if you have recorded an audio file for your photos, you can combine it with a playing slide show.

To view slide show :

First configure certain settings for the slide show. For details, please refer to **Picture Settings (Page43)**.

- A. Select pictures to be shown in slide show.
- B. Click Play button in the Control Panel. Slide show will start in full screen mode.

To view slide show in the View Window, click anywhere on your full screen.


To return to full screen view, click anywhere in the view window.

To stop a slide show in progress, do either of the followings:

- A. Click the Stop button on the Control Panel.
- B. Press Esc key on your keyboard.

Play Video Clips

Viewing video clips with XPC MAX provides full screen and high quality playback. You can select which video clip you want to view by clicking on the video thumbnail. Each video clip is shown as thumbnail, which provides easy selection. By default, Video Clips mode will load video clips stored in **My Documents > My Videos**. XPC MAX can import other video clips by adding the path to the **Media Library (Page41)**.



XPC MAX includes certain features to enhance your video clip viewing experience:

Sort By Name	Sort your video clips based on the video file name.
Sort By Date	Sort your video clips based on the date they were created.
Other Media	In addition to the video clips from Media Library, you can also watch video files in Shared Video and other removable devices attached to your computer. Double-click on the thumbnail to view video clips from other media.
Take Snapshot	You can take snapshot of video clips. When the image you like appears, click Take Snapshot bar to capture an still image of it.
View Snapshots	By default, all the still images that you have captured will be saved in Shared Pictures. To view the images that you have captured, click View Snapshots bar. You will be led into Picture Mode page, where the Captured Images folder shows as a thumbnail. Double-click on it to view the snapshots.


Music Mode

When you first enter Music mode, XPC MAX will load in music/audio files stored in **My Documents > My Music**. However, if you have music files stored in other folders and you want to listen to them, simply use **Media Library (Page41)**.



◆ *Listening to Music*

XPC MAX include cool features to enhance your audio experience and to suit your music style.



Songs	This first time you enter Music mode, it will scan music from the Media Library automatically. Click Songs bar, all music files scanned, including those in sub-folders, will be displayed by title order.
Albums	Sort your music files based on album. Music in the same album will be grouped together. Double-click on it to listen to music in the same album.
Artists	Sort your music files based on artist. Music by the same artist will be grouped together. Double-click on it to listen to music by the same artist.
Genres	Sort your music files based on genre. Music of the same genre will be grouped together. Double-click on it to listen to music of the same genre.
Go to Playlist	Listen to music from your playlist.
Add to Playlist	Add the selected songs to playlist.
Other Media	In addition to music files from Media Library, you can also organize & listen to music in CD or MP3 device. Click Other Media bar to load in or listen to music in other removable device attached to your machine.
Update Music	When you have made some changes to your music files, click Update Music to rescan your music files. Click the Update Music bar, it will search for music files immediately. Search Status & Files Found are displayed during and after searching process. Click Close bar to end thsi procedure.

To listen to music : Double-click on the music list or item that you want to listen to. Click the **Play**  button in the Control Panel. With XPC MAX you can also:

- ✓ **Repeat** : Listen to your selected music repeatedly.
- ✓ **Shuffle** : Listen to your selected music in random order.
- ✓ **Go to Playlist** : Organize your playlist in the Playlist Page.
- ✓ **Add to Playlist** : Add selected music to the playlist.

Note :

- 1. Each time you enter Music mode, it will auto select the playlist you were last listening to.**
- 2. To listen to your audio CD, insert the CD in your CD drive. You can also select it as the music source and organize songs in CD as well as those in your machine.**
- 3. XPC MAX supports Windows Media Audio,MP3,WAV files.**
- 4. To view music visualization while playing music, see details in General Settings. To change music visualization, click on the control panel.**

◆ **Playlist**

Using a playlist enables you to organize and arrange the way your music is played. With a playlist, you can sort music to suit your current mood. Want all smooth and relaxing music? Create a playlist with all your favorite adult contemporary to jazz.

XPC MAX provides various ways for you to create playlists. You can either create playlists from the already sorted music files or from all the music files found at the source.

To create a playlist :

1. First enter the music list, there are two ways to do so:
 - ✓ Click on **Albums/Artists/Genres** bar to get the sorted music list.
 - ✓ Click **Song** bar to show all music files in Media Library.
2. Select the music checkbox you want to include it in the playlist.
3. Click the **Add to Playlist** bar. After music imported into current playlist that you are editing, **Add to Playlist** bar will be grayed-out as a way to tell you importing work is done.
4. Click the **Go to Playlist** bar to view & also make sure the music you want has been imported successfully.
5. Now you are in the Playlist page, click **Save** bar to save your playlist.

To delete songs from a playlist :

Once a playlist has been saved it will exist forever. You can only temporarily delete songs from the playlist, rearrange the content of playlist and save it as another playlist.

1. From Music mode page, click **Go to Playlist** bar.
2. Click **Open Playlists** bar.
3. Double-click on the playlist that you want to delete. Click **Clear** bar.

To listen to music from previously saved playlist :


1. Click **Go to Playlist** bar to enter Playlist page.
2. Click **Open Playlists** bar to view a list of all playlists that you saved earlier.
3. Double-click on the playlist that you want to listen to, the songs will be auto loaded in. Click **the Play** button in the control panel to start enjoying music.

✍ Listening to the Radio

XPC MAX provides radio features so you can set a list of frequently-listened to radio stations or a list of your favorite radio stations. Each time when you feel like listening to radio, just click on the preset radio station. XPC MAX also lets you sort radio stations by name or by frequency. You can remove a preset ratio station at any time, and then have XPC MAX auto search your favorite radio station once again.

XPC MAX includes several features to enhance your listening experience:





My Favorite	You can save your favorite stations from the My Station list. Click on My Favorite bar, it will lead you to your Favorite Station List page where all your favorite stations added are listed here.
Add To Favorite	Click the checkbox to select the stations you want to add to your favorite station list. Sort by Name Sort your radio station by name.
Sort by Name	Sort your radio station by Name.
Sort by Freq	Sort your radio station by frequency.
Add Station	Scan for the desired radio station, click Add Station bar to add the station to your Station List.
Recorded Radio	You can record radio shows, news, songs you like or any piece from the radio. Click on Recorded Radio it will lead you to Music page. Rescan your music files before listening to a recorded radio piece.
Remove Station	No longer like a particular radio station? Click the checkbox of that radio station on the Station List, then click Remove Station bar to delete it.
Settings	Choose Radio Band: FM or AM here and then rescan channels to find new radio stations.

To listen to radio :

Double-click on the radio station that you want to listen to from the Radio List. Alternatively, click on the checkbox of the radio station that you want to listen to, and then click on the control panel.

Note : To record radio, click  on the control panel.

Appendix

BIOS Settings

The FB83 BIOS ROM has a built-in Setup program that allows users to modify basic system configuration. This information is stored in battery-backed RAM so that it retains Setup information even if the system power is turned off.

The system BIOS manages and executes a variety of hardware related functions including:

System date and time

Hardware execution sequence

Power management functions

Allocation of system resources

Enter the BIOS

To enter the BIOS (Basic Input / Output System) utility, follow these steps:

- Step1.** Power on the computer. The system will perform its POST (Power-On Self Test) routine checks.
- Step2.** Press the key immediately, or at the following message: Press DEL to enter SETUP, or simultaneously press <Ctrl>, <Alt>, <Esc> keys

Note 1. If you miss trains of words mentioned in step2 (the message disappears before you can respond) and you still wish to enter BIOS Setup, restart the system and try again by turning the computer OFF and ON again or by pressing the <RESET> switch located at the computer's front-panel. You may also reboot by simultaneously pressing the <Ctrl>, <Alt>, keys simultaneously.


Note 2. If you do not press the keys in time and system does not boot, the screen will prompt an error message, and you will be given the following options:

"Press F1 to Continue, DEL to Enter Setup"

- Step3.** When you enter the BIOS program, the CMOS Setup Utility will display the Main Menu, as shown in the next section.

The Main Menu

Once you enter the AwardBIOS(tm) CMOS Setup Utility, the Main Menu will appear on the screen. The Main Menu allows you to select from several setup functions and two exit choices. Use the arrow keys to select among the items and press <Enter> to accept and enter the sub-menu.



Note that a brief description of each highlighted selection appears at the bottom of the screen.

Setup Items

The main menu includes the following main setup categories. Recall that some systems may not include all entries.

Standard CMOS Features

Use this menu for basic system configuration.

Advanced BIOS Features

Use this menu to set the Advanced Features available on your system.

Advanced Chipset Features

Use this menu to change the values in the chipset registers and optimize your system's performance.

Integrated Peripherals

Use this menu to specify your settings for integrated peripherals.

Power Management Setup

Use this menu to specify your power management settings.

PnP / PCI Configurations

This entry appears if your system supports PnP / PCI.

PC Health Status

This entry displays the current system temperature, Voltage, and FAN settings.

Frequency/Voltage Control

Use this menu to specify your settings for frequency/voltage control.

Load Fail-Safe Defaults

Use this menu to load the BIOS default values for the minimal/stable performance of your system to operate.

Load Optimized Defaults

Use this menu to load the BIOS default values that are factory-set for optimal system operation. While Award has designed the custom BIOS to maximize performance, the factory has the right to change these defaults to meet users' needs.

Set Supervisor / User Password

Use this menu to change, set, or disable password protection. This allows you to limit access to the system and Setup, or only to Setup.

Save & Exit Setup


Save CMOS value changes in CMOS and exit from setup.

Exit Without Saving

Abandon all CMOS value changes and exit from setup.

Standard CMOS Features

The items in the Standard CMOS Setup Menu are divided into several categories. Each category includes none, one or more than one setup items. Use the arrow keys to highlight the item and then use the <PgUp> or <PgDn> keys to select the value you want in each item.



Date

<Month> <DD> <YYYY>

Set the system date. Note that the 'Day' automatically changes when you set the date.

Time

<HH : MM : SS>

The time is converted based on the 24-hour military-time clock.

For example, 5 p.m. is 17:00:00.

IDE Channel Master/Slave

Options are in its sub-menu.

Press <Enter> to enter the sub-menu of detailed options.

Drive A

Select the type of floppy disk drive installed in your system.

- The choice: None, 360K, 5.25 in, 1.2M, 5.25 in, 720K, 3.5 in, 1.44M, 3.5 in, or 2.88M, 3.5 in.

Video

Select the default video device.

- The choice: EGA/VGA, CGA 40, CGA 80, or MONO.

Halt On

Select the situation in which you want the BIOS to stop the POST process and notify you.

- The choice: All Errors, No Errors, All, But Keyboard, or All, But Diskette, All, But Disk/Key.

Base Memory

Displays the amount of conventional memory detected during boot up.

- The choice: N/A.

Extended Memory

Displays the amount of extended memory detected during boot up.

- The choice: N/A.

Total Memory

Displays the total memory available in the system.

- The choice: N/A.

IDE Adapters

The IDE adapters control the hard disk drive. Use a separate sub-menu to configure each hard disk drive.

IDE HDD Auto-Detection

Press <Enter> to auto-detect HDD on this channel. If detection is successful, it fills the remaining fields on this menu.

- Press Enter

IDE Channel Master/Slave

Selecting 'manual' lets you set the remaining fields on this screen and select the type of fixed disk. "User Type" will let you select the number of cylinders, heads, etc., Note: PRECOMP = 65535 means

NONE!

- The choice: None, Auto, or Manual.

Access Mode

Choose the access mode for this hard disk.

- The choice: CHS, LBA, Large, or Auto.

Capacity

Disk drive capacity (Approximated). Note that this size is usually slightly greater than the size of a formatted disk given by a disk checking program.

- Auto-Display your disk drive size.

The following options are selectable only if the 'IDE Primary Master' item is set to 'Manual', and Access mode set to CHS.

Cylinder

Set the number of cylinders for this hard disk.

- Min = 0, Max = 65535

Head

Set the number of read/write heads.

- Min = 0, Max = 255

Precomp

Warning: Setting a value of 65535 means no hard disk.

- Min = 0, Max = 65535

Landing zone

Set the Landing zone size.

- Min = 0, Max = 65535


Sector

Number of sector per track.

- Min = 0, Max = 255

Advanced BIOS Features

This section allows you to configure your system for basic operation. You have the opportunity to select the system's default speed, boot-up sequence, keyboard operation, shadowing, and security.



CPU Feature

Options are in its sub-menu.

Press <Enter> to enter the sub-menu of detailed options.

Delay Prior to Thermal

This item is select Delay Prior to Thermal.

- The Choice: 4Min, 8Min, 16Min or 32 Min.

Thermal Management

This item is select Thermal Management . Thermal Monitor 1 (On die throttling). Thermal Monitor 2 Ratio & VID transition).

- The Choice: Thermal Monitor 1 or Thermal Monitor 2.

TM2 Bus Ratio

Represents the frequency (bus ratio of the throttled performance statethat will be initiated when the on-diesensor gose from not hot to hot.

- The Choice: Min = 0 Max = 255.

Note: CPU support TM2, item appear.

TM2 Bus VID

Represents the voltage of the throttled performance state that will be initiated when the on die sensor goes from not hot to hot.

- The Choice: 0.8375V ~ 1.6000V.

Note: CPU support TM2, item appear.

Limit CPUID MaxVal

Set Limit CPUID MaxVal to 3, Should Be "Disabled" for WinXp.

- The Choice: Disabled or Enabled.

Note: Some older O.S.'s (Win98, WinMe..) cannot handle a CPUID MaxVal greater than 3. Please choose "Enabled" if you use one of those O.S. If your O.S. is WinXP or Win2000, we suggest you "Disabled" the item.

NX BIOS Control

When disabled, forces the NX feature flag to always return 0.

- The Choice: Enabled or Disabled.

Hard Disk Boot Priority

This item allows you to select Hard Disk Boot Device Priority.

Bios Write Protect

This item allows you to enable or disable the Bios Write Protect. If you want to flash BIOS, you must set it [Disabled].

- The choice: Enabled or Disabled.

Virus Warning

Allows you to choose the VIRUS Warning feature for IDE Hard Disk boot sector protection. If this function is enabled and someone attempts to write data into this area, BIOS will show a warning message on screen, and an alarm beep.

Enabled Activates automatically when the system boots up, causing a warning message to appear when anything attempts to access the boot sector or hard disk partition table.

Disabled No warning message will appear when anything attempts to access the boot sector or hard disk partition table.

- The choice: Enabled or Disabled.

CPU L1&L2&L3 Cache

All processors that can be installed in this mainboard use internal level1 (L1) , external 2(L2) and (L3) cache memory to improve performance.

Leave this item at the default value for better performance.

- The choice: Enabled or Disabled.

Note : CPU support, L3 item appear.

Hyper-Threading Technology

The latest Intel application defines a high-speed calculating ability to optimize your system by two CUPs supported(one virtual, one physical) in a multi-task environment. "Enabled" for Windows XP and Linux 2.4.x (OS optimized for Hyper Threading Technology and "Disable" for other OS(OS not optimized for Hyper Threading Technology)

- The choice: Enabled, or Disabled.

Quick Power On Self Test

This item speeds up Power-On Self Test (POST) after you power on the computer. If it is set to enabled, BIOS will shorten or skip some check items during POST.

- The choice: Enabled, or Disabled.

First/Second/Third Boot Device

The BIOS attempts to load the operating system from the devices in the sequence selected in these items.

- The Choice: LS120, Hard Disk, CDROM, ZIP100, USB-FDD, USB-ZIP,USB-CDROM, LAN, Disabled or Floppy.

Boot Other Device

If BIOS can't load O.S. from First/Second/Third boot device you select above, BIOS will search other devices and attempt to load O.S..

- The choice: Enabled or Disabled.

Boot Up Floppy Seek

Enabled tests floppy drives to determine whether they have 40 or 80 tracks

- The choice: Enabled or Disabled.

Boot Up NumLock Status

Selects power on state for NumLock.

- The choice: Off or On.

Gate A20 Option

This entry allows you to select how the Gate A20 is handled. The gate A20 is a device used for above 1MByte of address memory. Initially, the gate A20 was handled via a pin on the keyboard. Today, while a keyboard still provides this support, it is more common and much faster in setting to fast for the system chipset to provide support for gate A20.

- The choice: Normal or Fast.

Typematic Rate Setting

Keystrokes repeat at a rate determined by the keyboard controller. When this controller enabled, the typematic rate and typematic delay can be selected.

- The choice: Enabled or Disabled.

Typematic Rate (Chars/Sec)

This item sets how many times the keystroke will be repeat in a second when you hold the key down.

- The choice: 6, 8, 10, 12, 15, 20, 24, or 30.

Typematic Delay (Msec)

Sets the delay time after the key is held down before it begins to repeat the keystroke.

- The choice: 250, 500, 750, or 1000.

Security Option

Select whether the password is required every time the system boots or only when you enter setup.

System The system will not boot and access to Setup will be denied if the correct password is not entered promptly.

Setup The system will boot, but access to Setup will be denied if the correct password is not entered promptly.

- The choice: System or Setup.

Note : To disabled security, select **PASSWORD SETTING** at Main Menu, and then you will be asked to enter password. Don't type anything and just press < Enter > ; it will disable security. Once the security is disabled, the system will boot, and you can enter Setup freely.

APIC Mode

Via the routing, I/O APIC support a total of 24 interrupts. We recommend to choose [Enabled] for Windows XP and Windows 2000.

- The choice: Enabled or Disabled.

MPS Version Control For OS

Selects the operating system multiprocessor support version.

- The choice: 1.1 or 1.4

Delay For HDD <Secs>

This item allows you to set delay for HDD <secs> .

- The choice: 0~ 15.

Small Logo(EPA) Show

This item allows you to enable/disable the EPA Logo.

- The choice: Enabled or Disabled.

Advanced Chipset Features

This section allows you to configure the system based on the specific features of the installed chipset. This chipset manages bus speeds and access to system memory resources, such as DRAM and the external cache. It also coordinates communications between the conventional ISA bus and the PCI bus. It states that these items should never need to be altered.

The default settings have been chosen because they provide the best operating conditions for your system. If you discovered that data was being lost while using your system, you might consider making any changes.

Phoenix - AwardBIOS CMOS Setup Utility		Item Help
Advanced Chipset Features		Menu Level ▶
System BIOS Cacheable	[Enabled]	
Video BIOS Cacheable	[Disabled]	
Memory Hole At 15M-16M	[Disabled]	
*** UGA Setting ***		
PEG/Onchip UGA Control	[Auto]	
PEG Force X1	[Disabled]	
On-Chip Video Memory Size	[Press Enter]	
On-Chip Frame Buffer Size	[8MB]	
DUMT Version	[DUMT 3.0]	
FIXED Memory Size	[24MB]	
DUMT Memory Size	[63MB]	
↑↓:Move Enter:Select +/-/PU/PD:Value F10:Save ESC:Exit F1:General Help F5: Previous Values F6: Fail-Safe Defaults F7: Optimized Defaults		

System BIOS Cacheable

Selecting Enabled allows caching of the system BIOS ROM at F0000h ~ FFFFFh, resulting in better system performance. However, if any program is written to this memory area, a system error may result.

- The Choice: Enabled or Disabled.

Video BIOS Cacheable

Selecting Enabled allows caching of the video BIOS, resulting in better system performance. However, if any program is written to this memory area, a system error may result.

- The Choice: Enabled or Disabled.

Memory Hole At 15M-16M

You can reserve this area of system memory for ISA adapter ROM. When this area is reserved, it can't be cached. The user information of peripheral

als that need to use this area of system memory usually discusses their memory requirements.

- The Choice: Enabled or Disabled.

***** **VGA Setting** *****

PEG/Onchip VGA Control

This item allows you to decide to activate whether PEG slot or Onchip VGA first.

- The choice: Auto, Onchip VGA or PEG Port .

PEG Force X1

This item allows you to force PEG link X1.

- The Choice: Enabled, or Disabled.

On-Chip Video Memory Size

Press <Enter> to set the On-Chip Video memory size.

On-Chip Frame Buffer Size

This item allows you to set the onboard VGA share memory size.

- The Choice: 1MB or 8MB.

DVMT Version

This item allows you to set the DVMT Version.

- The Choice: DVMT 3.0.

FIXED Memory Size

This item allows you to set the FIXED Memory Size.


- The Choice: 0MB, 24MB, 31MB, 56MB, 63MB, 120MB or 127MB.

DVMT Memory Size

This item allows you to set the DVMT Memory Size.

- The Choice: MAX.DVMT, 0MB, 24MB, 31MB, 56MB, 63MB, 120MB or 127MB.

Integrated Peripherals



On-Chip IDE Device

Options are in its sub-menu.

Press <Enter> to enter the sub-menu of detailed options.

IDE HDD Block Mode

If your IDE hard disk drive supports block mode (most new drives do), select Enabled to automatically detect the optimal number of block reads and writes per sector that the drive can support and improves the speed of access to IDE devices.

- The choice: Enabled, or Disabled.

IDE DMA transfer access

Improve IDE HD/CDROM transfer performance.

- The choice: Enabled or Disabled.

On-Chip Primary PCI IDE

Use these items to enable or disable the PCI IDE channels that are integrated on the mainboard.

- The choice: Enabled or Disabled.

IDE Primary Master/Slave PIO

Each IDE channel supports a master device and a slave device. These four items let you assign which kind of PIO (Programmed Input / Output) is used by IDE devices. Choose Auto to let the system auto detect which PIO mode is best or select a PIO mode from 0-4.

- The choice: Auto, Mode 0, Mode 1, Mode 2, Mode 3, or Mode 4.

IDE Primary Master/Slave UDMA

Each IDE channel supports a master device and a slave device. This mainboard supports UltraDMA technology, which provides faster access to IDE devices.

If you install a device that supports UltraDMA, change the appropriate item on this list to Auto. You may have to install the UltraDMA driver supplied with this mainboard in order to use an UltraDMA device.

- The Choice: Auto or Disabled.

***** **On -Chip Serial ATA Setting** *****

SATA Mode


This item allows you to set the SATA Mode.

- The choice: IDE, RAID or AHCI.


On-Chip Serial ATA

- The Choice: Disabled, Enhanced Mode or SATA Only.


Disabled : Disabled SATA Controller.



Enhanced Mode: Enables both SATA and PATA. Max. 2 ATA drives are supported. Some current operating systems (WinXP, Windows NET Server, Windows 2000) support Enhanced mode.



SATA-Only :SATA operates in legacy mode.



SATA Hot-Plug

This item allows you to set the SATA Hot-Plug.

- The choice: Disabled or Enabled.

Onboard Device

Options are in its sub-menu.

Press <Enter> to enter the sub-menu of detailed options.

USB Controller

Select Enabled if your system contains a Universal Serial Bus (USB) port on this mainboard.

- The choice: Enabled or Disabled.

USB 2.0 Controller

Select Enabled if your system contains a Universal Serial Bus (USB) 2.0 controller and you have USB peripherals.

- The choice: Enabled or Disabled.

AC97 Audio

This item allows you to select AC 97 audio chip to support Audio. Disable this item if you are going to install a PCI audio add-on card.

- The Choice: Auto or Disabled.

SuperIO Device

Options are in its sub-menu.

Press <Enter> to enter the sub-menu of detailed options.

Onboard FDC Controller

This item specifies onboard floppy disk drive controller. This setting allows you to connect your floppy disk drives to the onboard floppy connector.

- The choice: Enabled or Disabled.

Onboard Serial Port 1

This option is used to assign the I/O address and interrupt request (IRQ) for the onboard serial port 1 (COM1).

- The choice: Disabled, 3F8/IRQ4, 2F8/IRQ3, 3E8/IRQ4, 2E8/IRQ3, or Auto.

Onboard Infrared Port

This option is used to assign the I/O address and interrupt request (IRQ) for the onboard infrared port.

- The choice: Disabled, 3F8/IRQ4, 2F8/IRQ3, 3E8/IRQ4, 2E8/IRQ3 or Auto.

UART Mode Select

This field is available if the Onboard Serial Port 2 field is set to any option but disabled. UART Mode Select enables you to select the infrared communication protocol-Normal (default), IrDA, or ASKIR. IrDA is an infrared communication protocol with a maximum baud rate up to 115.2K bps. ASKIR is Sharp's infrared communication protocol with a maximum baud rate up to 57.6K bps.

- The choice: SCR, IrDA or ASKIR .

UR2 Duplex Mode

This item is available when UART 2 mode is set to either ASKIR or IrDA. This item enables you to determine the infrared function of the onboard infrared chip. The options are Full and Half (default).

Full-duplex means that you can transmit and send information simultaneously. Half-duplex is the transmission of data in both directions, but only one direction at a time.

- The choice: Full or Half.

Onboard Parallel Port

This item allows you to determine onboard parallel port controller I/O address and interrupt request (IRQ).

- The choice: 378/IRQ7, 278/IRQ5, 3BC/IRQ7, or Disabled.

Parallel Port Mode

Select an operating mode for the onboard parallel (printer) port. Select Normal, Compatible, or SPP unless you are certain your hardware and software both support one of the other available modes.

- The choice: SPP, EPP, ECP, or ECP + EPP.

ECP Mode Use DMA

When the onboard parallel is set to ECP mode, the parallel port can use DMA3 or DMA1.

- The choice: 1 or 3.

Power Management Setup

Phoenix - AwardBIOS CMOS Setup Utility		Item Help
Power Management Setup		Menu Level ▶
ACPI Function	Enabled	
ACPI Suspend Type	[S3<STR>]	
Run VGABIOS if S3 Resume	[Auto]	
Power Management	[User Define]	
Video Off Method	[U/H SYNC+Blank]	
Video Off In Suspend	[Yes]	
Suspend Type	[Stop Grant]	
MODEM Use IRQ	[3]	
Suspend Mode	[Disabled]	
HDD Power Down	[15 Min]	
Soft-Off by PWR-BTN	[Instant-Off]	
Wake-Up by PCI card	[Disabled]	
Power On by Ring	[Disabled]	
USB KB/MS Wake-Up From S3	[Disabled]	
Resume by Alarm	[Enabled]	
Date(of Month) Alarm	[0]	
Time(hh:mm:ss) Alarm	0 : 0 : 0	
** Reload Global Timer Events **		
Primary IDE 0	[Disabled]	
Primary IDE 1	[Disabled]	
FDD,COM,LPT Port	[Disabled]	
PCI PIRQ[A-D]#	[Disabled]	
PS2 Keyboard Power ON	[Password]	
KB Power ON Password	[Enter]	
Hot Key Power ON	[Ctrl-F12]	
PS2 Mouse Power ON	[Disabled]	
PWRON After PWR-Fail	[Off]	

↑↓:Move Enter:Select +/-/PU/PD:Value F10:Save ESC:Exit F1:General Help
 F5: Previous Values F6: Fail-Safe Defaults F7: Optimized Defaults

The Power Management Setup allows you to configure your system to most effectively save energy while operating in a manner consistent with your computer usage.

ACPI Function

This item allows you to enable/disable the Advanced Configuration and Power Management (ACPI).

- Always "Enabled".

ACPI Suspend Type

This item allows you to select sleep state when suspend.

- The choice: S1(POS), S3(STR), or S1 & S3.

Run VGABIOS if S3 Resume(Auto)

This item allows the system to initialize the VGA BIOS from S3(Suspend to RAM) sleep state.

- The choice: Auto, Yes or No.

Power Management

This item allows you to decide the timing to enter suspend mode.

- The choice: User Define, Min Saving, Max Saving.

Video Off Method

This determines the manner in which the monitor is blanked.

V/H SYNC + Blank This selection will cause the system to turn off the vertical and horizontal synchronization ports and write blanks to the video buffer.

Blank Screen This option only writes blanks to the video buffer.

DPMS Initial display power management signaling.

- The choice: V/H SYNC + Blank, Blank Screen, or DPMS.

Video Off In Suspend

This item determines the manner in which the monitor is blanked.

- The choice: Yes or No.

Suspend Type

This item allows you to select the Suspend Type.

- The choice: Stop Grant or PwrOn suspend.

MODEM Use IRQ

This determines the IRQ which the MODEM can use.

- The choice: 3, 4, 5, 7, 9, 10, 11, or NA.

Suspend Mode

When this item enabled and after the set up time of system inactivity, all devices except the CPU will be shut off.

- The choice: Disabled, 1Min, 2Min, 4Min, 8Min, 12Min, 20Min, 30Min, 40Min, or 1Hour.

HDD Power Down

When this item enabled and after the set up time of system inactivity, the hard disk drive will be powered down while all other devices remain active.

- The choice: Disabled or 1 Min ~ 15 Min.

Soft-Off by PWR-BTTN

Under ACPI you can create a software power down. In a software power down, the system can be resumed by Wake UP Alarms. This item lets you install a software power down that is controlled by the power button on your system. If the item is set to Instant-Off, then the power button causes a software power down. If the item is set to Delay4 Sec. then you have to hold the power button down for 4 seconds to cause a software power down.

- The choice: Instant-Off or Delay 4 Sec.

Wake-Up by PCI card

This item Enabled/Disabled PCI Power Management Event to wake up system.

- The choice: Enabled or Disabled.

Power On by Ring

This item determine the system will resume by activating of modem ring.

- The choice: Enabled or Disabled.

USB KB/MS Wake-up From S3

If you are using a USB KB/MS, and the ACPI suspend type is set to S3, you can enable this item to allow a KB/MS to wake up the system from power saving mode.

- The choice: Enabled or Disabled.

Resume by Alarm

When this item enabled, your can set the date (day of the month) and time to turn on your system.

- The choice: Disabled or Enabled.

Date(of Month) Alarm

This item selects the alarm Date (day of the month).

- Key in a DEC number: Min = 0, Max = 31.

Time(hh : mm : ss) Alarm

This item selects the alarm Time.

- [hh] ➤ Key in a DEC number: Min = 0, Max = 23.

- [mm/ss] ➤ Key in a DEC number: Min = 0, Max = 59.

***** Reload Global Timer Events *****

Global Timer (power management) events are I/O events whose occurrence can prevent the system from entering a power saving mode or can awaken the system from such as a mode. In effect, the system remains alert for anything that occurs to a device that is configured as Enabled, even when the system is in a power-down mode.

Primary IDE 0/1

When these items are enabled, the system will restart the power-saving time out counters when any activity is detected on any of the drives or devices on the primary or secondary IDE channels.

- The choice: Disabled or Enabled.

FDD, COM, LPT Port

When this item is enabled, the system will restart the power-saving timeout counters when any activity is detected on the floppy disk drive, serial ports, or the parallel port.

- The choice: Disabled or Enabled.

PCI PIRQ [A-D] #

When this item is disabled, any PCI device set as the Master will not power on the system.

- The choice: Disabled or Enabled.

PS2 Keyboard Power ON

This item allows you to set the PS2 Keyboard Power On function.

- The choice: Disabled, Password, or Hot Key.

KB Power ON Password

This item allows you to set the KB Power On Password.

- Press "Enter" to set Password.

Hot Key Power On

This item allows you to set the Hot Key Power On.

- The choice: Any Key, Ctrl-F1 ~ Ctrl-F12.

PS2 Mouse Power ON

This item allows you to enable or disable the PS2 Mouse Power On.

- The choice: Disabled or Enabled.

Pwron After PWR-Fail

This item defines if the system will be rebooted after the power fails.

- The choice: Off, On, Former-Sts.

PnP/PCI Configurations

Phoenix - AwardBIOS CMOS Setup Utility		
PnP/PCI Configurations		
Init Display First	[PCI Slot]	Item Help Menu Level ▶
Reset Configuration Data	[Disabled]	
Resources Controlled By	[Auto<ESCD>]	
x IRQ Resources	Press Enter	
PCI/UGA Palette Snoop	[Disabled]	
INT Pin 1 Assignment	[Auto]	
INT Pin 2 Assignment	[Auto]	
INT Pin 3 Assignment	[Auto]	
INT Pin 4 Assignment	[Auto]	
INT Pin 5 Assignment	[Auto]	
INT Pin 6 Assignment	[Auto]	
INT Pin 7 Assignment	[Auto]	
INT Pin 8 Assignment	[Auto]	
** PCI Express relative items **		
Maximum Payload Size	[4096]	
↑↓←:Move Enter:Select +/~/PU/PD:Uvalue F10:Save ESC:Exit F1:General Help F5: Previous Values F6: Fail-Safe Defaults F7: Optimized Defaults		

This section describes the configuration of PCI bus system. PCI or Personal Computer Interconnection is a system which allows I/O devices to operate at the speed CPU itself keeps when CPU communicating with its own special components.

This section covers some very technical items, and it is strongly recommended that only experienced users should make any changes to the default settings.

Init Display First

This item allows you to decide to activate whether PCI slot or PCIEx first.

- The Choice: PCI Slot, Onboard or PCIEx.

Reset Configuration Data

Normally, you leave this field Disabled. Select Enabled to reset Extended System Configuration Data (ESCD) when you exit from Setup if you have installed a new device or software and the system reconfiguration has caused such a serious conflict that the operating system can not boot.

- The choice: Enabled or Disabled .

Resource controlled By

The Award Plug-and-Play BIOS has the capacity to automatically configure all of the boot and Plug-and-Play compatible devices. However, this capability means absolutely nothing unless you are using a Plug-and-Play operating system such as Windows 95.

If you set this field to "manual" , choose specific resources by going into each of the sub-menu that follows this field (a sub-menu is proceeded by a ">").

- The choice: Auto(ESCD) or Manual.

IRQ Resources

When resources are controlled manually, assign each system interrupt a type, depending on the type of device using the interrupt.

IRQ3/4/5/7/10/11/12/14/15 assigned

This item allows you to determine the IRQ assigned to the ISA bus and is not available to any PCI slot. Legacy ISA for devices is compliant with the original PC AT bus specification; PCI/ISA PnP for devices is compliant with the Plug-and-Play standard whether designed for PCI or ISA bus architecture.

- The choice: PCI Device or Reserved.

PCI/VGA Palette Snoop

It determines whether the MPEG ISA/VESA VGA Cards can work with PCI/VGA or not. If you have MPEG ISA/VESA VGA Cards and PCI/VGA Card worked, Enable this field. Otherwise, please Disable it.

- The choice: Enabled or Disabled.

INT Pin1 ~ 8 Assignment

Names the interrupt request(IRQ) line assigned to a device connected to the PCI interface on your system.

- The choice: Auto, 3, 4, 5, 7, 9, 10, 11, 12, 14, 15.

***** **PCI Express relative items** *****

Maximum Payload Size

Set maximum TLP payload size for the PCI Express devices.
The unit is byte.

- The choice: 4096, 2048, 1024, 512, 256 or 128.



PC Health Status

Phoenix - AwardBIOS CMOS Setup Utility PC Health Status		
CPU Fan Speed Control	[Smart Fan]	Item Help
CPU Temp Tag	[60 °C]	Menu Level ▶
CPU Voltage		Choice Cpu Fan
ChipSet Voltage		Temp Speed
+3.3V		<Ultra> ↑75 °C Full
+5V		Low ↓75 °C <U>L
+12V		Mid ↑75 °C Full
-12V		↓75 °C Mid
DDR Voltage		Full always Full
+5USB		Smart Fan : base on
Voltage Battery		Cpu Temp to adjust
System Temperature		Fan Speed.
CPU Temperature		
PWM Temperature		
Fan 1 Speed		
Fan 2 Speed		
Fan 3 Speed		
↑↓:Move Enter:Select +/-/PU/PD:Ualue F10:Save ESC:Exit F1:General Help F5: Previous Values F6: Fail-Safe Defaults F7: Optimized Defaults		

CPU Fan Speed Control

Here you can set the ICE Fan Speed.

- The choice: Smart Fan, Ultra-Low, Low, Mid, or Full.

Note : Before manually modifying the CPU fan setting, please make sure fan connectors are plugged into the correct fan connector on the mainboard.

Choice	Cpu Temp	Fan Speed
<Ultra> Low	↑75 °C ↓75 °C	Full <U>L
Mid	↑75 °C ↓75 °C	Full Mid
Full	always	Full

Smart Fan : base on Cpu Temp to adjust Fan Speed.

Ultra-Low	CPU Temperature below 80 °C , fan spins at 900 rpm.
	CPU Temperature over 80 °C , fan spins at 3800 rpm.
Low	CPU Temperature below 80 °C , fan spins at 1500 rpm.
	CPU Temperature over 80 °C , fan spins at 3800 rpm.
Mid	CPU Temperature below 80 °C , fan spins at 2100 rpm.
	CPU Temperature over 80 °C , fan spins at 3800 rpm.
Full	CPU fan always spins at 3800 rpm.

CPU Temp Tag

This item is only for Shuttle's unique 'Smart Fan' temperature control program. Temp tag lets you specify your optimal CPU temperature, then 'Smart Fan' takes over and controls the fan rpm accordingly. Choose a temperature setting between 25°C and 75°C, in a 1°C increment.

➤ The choice: 25 ~ 75 °C.

Current CPU Temp Over CPU Temp Tag	Fan Speed (rpm)
OVER 0 °C	950
1 °C	1050
2 °C	1150
3 °C	1250
4 °C	1450
5 °C	1550
6 °C	1650
7 °C	1800
8 °C	1950
9 °C	2100
10 °C	2200
11 °C	2300
:	:
:	:

Smart Fan : base on Cpu Temp dynamic adjust Fan Speed. When CPU Temp over 75 °C, fan speed full.

CPU Voltage

ChipSet Voltage

+ 3.3V

+ 5V

+ 12V

-12V

DDR Voltage

+ 5VSB

Voltage Battery

System Temperature

CPU Temperature

PWM Temperature

Fan 1 Speed

Fan 2 Speed

Fan 3 Speed

Warning : It is Strongly recommended to disable 'Smart Fan' if you use an alternative fan to the default.

Frequency/Voltage Control

Phoenix - AwardBIOS CMOS Setup Utility		Frequency/Voltage Control	
Auto Detect PCI Clk	[Enabled]	▲	Item Help
Spread Spectrum	[Enabled]		
DRAM Timing Selectable	[By SPD]		
CAS Latency Time	[Auto]		
DRAM RAS# to CAS# Delay	[Auto]		
DRAM RAS# Precharge	[Auto]		
Precharge delay (tRAS)	[Auto]		
System Memory Frequency	[Auto]		
Refresh Mode Select	[Auto]		
***** Clock *****			
Now CPU Frequency			
Now DDR Frequency			
CPU Clock Ratio	[8 X]		
CPU Ratio Fixed 14x	[Disabled]		
CPU Clock	[200MHz]		
***** Voltage *****			
CPU Voltage set	[Auto]		
DDR Voltage set	[Auto]		
ChipSet Voltage set	[Auto]		
▲▼:Move Enter:Select +/-/PU/PD:Ualue F10:Save ESC:Exit F1:General Help F5: Previous Values F6: Fail-Safe Defaults F7: Optimized Defaults			

Auto Detect PCI Clk

This item allows you to auto enable/disable an empty PCI Slot Clock.

- The choice: Enabled or Disabled.

Spread Spectrum

This item allows you to enable or disable the spread spectrum modulation.

- The choice: Disabled or Enabled.

DRAM Timing Selectable

The value in this field depends on performance parameters of the installed memory chips(DRAM). It is recommended that you don't change the value from the factory setting unless you install new memory that has a different performance rating than the original DRAMs.

- The Choice: Manual or BySPD

CAS Latency Time

When synchronous DRAM is installed, the number of CAS latency clock cycles depends on the DRAM timing. It is recommended don't change this field from the default value specified.

- The Choice: Auto, 2, 2.5, or 3.

DRAM RAS # to CAS # Delay

This field lets you insert a timing delay between the CAS and RAS strobe

signals when DRAM is written to, read from, or refreshed. Faster performance is gained at high speed, more stable performance, at low speed. This field is applied only when synchronous DRAM is installed in the system.

- The Choice: Auto, 5, 4, 3 or 2.

DRAM RAS # Precharge

If an insufficient number of cycles is allowed for the RAS to accumulate its charge before DRAM refresh, the refresh may not complete, and the DRAM may fail to retain data. High gives faster performance; and Slow gives more stable performance. This field is applicable only when synchronous DRAM is installed in the system.

- The Choice: Auto, 5, 4, 3 or 2.

Precharge delay (tRAS)

This item allows you to set Precharge delay (tRAS).

- The Choice: 4 ~ 15 or Auto.

System Memory Frequency

This item allows you to set System Memory Frequency.

- The Choice: 333MHz, 400MHz or Auto.

Refresh Mode Select

This item allows you to select Refresh Mode.

- The Choice: Auto, 7.8us, 15.6us or 64us.

***** **Clock** *****

Now CPU Frequency : Show now CPU frequency.

Now DDR Frequency: Show now DDR is DDR333 or DDR400, singal or dual channel.

CPU Clock Ratio

This item allows the user to adjust CPU Clock Ratio.
If CPU is unlocked, item appear.

- The Choice: 8X ~ 50X.

CPU Ratio Fixed 14x

Select "Enabled" to fixed CPU ratio 14.

Note:Only support CPU FSB800 3.4/3.6/3.8 or above.

Select "Disabled",CPU ratio run native mode.

- The choice: Disabled or Enabled.

CPU Clock

This item allows the user to adjust CPU Host Clock.

Min: 100 Max: 355

- Key in a DEC number: (Between Min and Max.)

***** **Voltage** *****

CPU Voltage

This item allows you to set CPU Voltage.

- The choice: 0.825V ~ 1.5875V or Auto.

DDR Voltage

This item allows you to set DDR Voltage.

- The choice: Auto, 2.70V, 2.80V or 2.90V.

ChipSet Voltage set

This item allows you to set ChipSet Voltage.

- The choice: Auto, 1.60V or 1.70V.



Load Fail-Safe Defaults

When you press <Enter> on this item, you will get a confirmation dialog box with a message similar to:

Load Fail-Safe Defaults (Y/N) ? N

Pressing 'Y' loads the BIOS default values for the most stable, minimal system performance.



Load Optimized Defaults


When you press <Enter> on this item, you will get a confirmation dialog box with a message similar to:

Load Optimized Defaults (Y/N) ? N

Pressing 'Y' loads the default values that are factory-set for optimal system performance.



Set Password



This item is to set a supervisor password. Please follow below steps.

New Password Setting:

1. Press the <Enter> key. A dialog box appears to ask you to "Enter password: ".
2. Key in a new password.
The password can not be over eight characters or numbers.
3. The system will then request you to confirm the new password by asking you to key in the new password again.
4. Once the confirmation is completed, new code is in effect.

No Password Setting:

5. If you want to delete the password, just press the <Enter> key instead of typing a new password. Follow the procedure as above.

If You Forget Password:

6. If you forget your password, you must turn off the system and clear CMOS.
Please refer to the tech notes at the end of section two for more information.



Save & Exit Setup

Press <Enter> on this item to save your changes. The system will ask for confirmation : system

Save to CMOS and EXIT (Y/N)? Y

Pressing "Y" stores the selections made in the menus of CMOS - a special section of memory that stays on after you turn your system off. The next time you boot your computer, the BIOS configures your system according to the Setup selections stored in CMOS. After saving the values the system will restart.



Exit Without Saving

Press <Enter> on this item to exit without saving changes. The system will ask for confirmation:

Quit without saving (Y/N)? Y

This allows you to exit from Setup without storing in CMOS any change. The previous selections remain in effect. This exits from the Setup utility and restarts your computer.

xpc

By SHUTTLE

MEMO

.....

.....

.....

.....

.....

.....

.....

.....



www.shuttle.com

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

**XPC MAX
SB83G5C**